Package 'gp3ml'

October 22, 2026

Type Package

Title Governance-First Predictive Modelling for 'Gazepoint' Research

Version 0.3.2

Description Provides governance-first infrastructure for leakage-resistant predictive modelling and validation using 'Gazepoint'-derived research data. Supports explicit task and role declarations, feature-provenance manifests, group-aware holdout splitting and repeated resampling, repository-aware fold evaluation, explicit governed tuning, nested grouped resampling, fold-local preprocessing, discrimination and calibration metrics, target-aligned uncertainty, external-validation and transportability reports, prediction-to-decision governance, target-aware conformal prediction, dataset-shift auditing, locked analysis plans, portable model artifacts, robustness diagnostics, environment provenance, research-object export, model cards, and reproducibility evidence. Intended only for explicitly observed, non-sensitive outcomes and declared scientific purposes. Use is prohibited for person identification, biometric authentication, health or protected-attribute inference, and direct or indirect inference of emotion, stress, personality, deception, cognition, comprehension, intent, or other mental states.

License MIT + file LICENSE

Encoding UTF-8

Language en-US

Depends R (>= 4.1.0)

Suggests bundle, callr, openssl, renv, jsonlite, keras3, knitr, nnet, pkgdown, ranger, rmarkdown, testthat (>= 3.0.0), xgboost

VignetteBuilder knitr

RoxygenNote 8.0.0

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

URL https://stefanosbalaskas.github.io/gp3ml/, https://CRAN.R-project.org/package=gp3ml, https://github.com/stefanosbalaskas/gp3ml

BugReports https://github.com/stefanosbalaskas/gp3ml/issues

NeedsCompilation no

Author Stefanos Balaskas [aut, cre] (ORCID:
<https://orcid.org/0000-0003-2444-9796>)

Maintainer Stefanos Balaskas <s.balaskas@ac.upatras.gr>

Repository CRAN

Date/Publication 2026-10-22 11:50:11 UTC

Contents

apply_gazepoint_calibrator . . . 5
apply_gazepoint_decision_rule . . . 6
assert_gp3ml_engine_available . . . 7
assert_gp3ml_use_case . . . 7
assess_gazepoint_calibration . . . 8
assess_gazepoint_conformal_coverage . . . 9
as_gp3ml_data . . . 10
audit_gazepoint_abstention . . . 11
audit_gazepoint_dataset_shift . . . 11
audit_gazepoint_group_folds . . . 12
audit_gazepoint_missingness_shift . . . 13
audit_gazepoint_ml_leakage . . . 14
audit_gazepoint_model_robustness . . . 16
audit_gazepoint_nested_resampling . . . 17
audit_gazepoint_plan_deviations . . . 17
audit_gazepoint_reproducibility . . . 18
audit_gp3ml_api_stability . . . 19
audit_gp3ml_governance_profile . . . 19
bake_gazepoint_preprocessor . . . 20
bootstrap_gazepoint_metrics . . . 21
bootstrap_gazepoint_metrics_by_unit . . . 22
capture_gazepoint_environment . . . 24
collect_gazepoint_fold_predictions . . . 25
combine_gazepoint_handoffs . . . 25
compare_gazepoint_environments . . . 26
compare_gazepoint_models . . . 26
create_external_validation_report . . . 27
create_gazepoint_decision_rule . . . 28
create_gazepoint_feature_manifest . . . 30
create_gazepoint_group_folds . . . 31
create_gazepoint_handoff . . . 34
create_gazepoint_model_artifact . . . 35
create_gazepoint_model_card . . . 36
create_gazepoint_nested_folds . . . 37
create_gazepoint_release_evidence . . . 39
create_gazepoint_release_model_card . . . 40

create_gazepoint_reproducibility_report . . . 41
create_gazepoint_synthetic_manifest . . . 42
create_gazepoint_synthetic_task . . . 43
create_gazepoint_tuning_grid . . . 44
create_gp3ml_governance_profile . . . 45
declare_gazepoint_analysis_plan . . . 45
declare_gazepoint_external_dataset . . . 47
declare_gazepoint_task . . . 48
diagnose_gazepoint_group_folds . . . 50
evaluate_external_validation . . . 52
evaluate_gazepoint_external_transportability . . . 54
evaluate_gazepoint_feature_stability . . . 55
evaluate_gazepoint_group_folds . . . 55
evaluate_gazepoint_missingness_sensitivity . . . 57
evaluate_gazepoint_nested_resampling . . . 58
evaluate_gazepoint_seed_stability . . . 59
evaluate_gazepoint_thresholds . . . 59
evaluate_gazepoint_threshold_stability . . . 60
fit_gazepoint_calibrator . . . 61
fit_gazepoint_conformal . . . 62
fit_gazepoint_deep_model . . . 63
fit_gazepoint_model . . . 65
fit_gazepoint_preprocessor . . . 66
gazepoint_classification_metrics . . . 68
gazepoint_performance_metrics . . . 69
gazepoint_regression_metrics . . . 71
gp3ml_api_contracts . . . 71
gp3ml_available_engines . . . 72
gp3ml_engine_capabilities . . . 72
gp3ml_interop_contracts . . . 73
gp3ml_object_schema . . . 73
gp3ml_prohibited_uses . . . 74
integrate_black_box_model . . . 74
lock_gazepoint_analysis_plan . . . 76
normalize_gazepoint_artifact_text . . . 76
plot.gp3ml_abstention_audit . . . 77
plot.gp3ml_api_stability_audit . . . 77
plot.gp3ml_conformal_coverage . . . 78
plot.gp3ml_dataset_shift_audit . . . 78
plot.gp3ml_engine_capabilities . . . 79
plot.gp3ml_environment_comparison . . . 79
plot.gp3ml_governance_profile_audit . . . 80
plot.gp3ml_handoff_validation . . . 80
plot.gp3ml_model_artifact_validation . . . 81
plot.gp3ml_model_robustness_audit . . . 81
plot.gp3ml_plan_deviation_audit . . . 82
plot.gp3ml_release_checksum_validation . . . 82
plot.gp3ml_reproducibility_audit . . . 83

plot.gp3ml_research_bundle_validation . . . 83
plot.gp3ml_ro_crate_validation . . . 84
plot.gp3ml_threshold_evaluation . . . 84
predict.gp3ml_model . . . 85
predict_gazepoint_interval . . . 86
predict_gazepoint_set . . . 87
print.gazepoint_feature_manifest_validation . . . 87
print.gazepoint_fold_diagnostics . . . 88
print.gazepoint_fold_diagnostics_validation . . . 90
print.gazepoint_group_folds . . . 91
print.gazepoint_group_folds_audit . . . 93
print.gazepoint_group_folds_validation . . . 95
print.gazepoint_ml_leakage_audit . . . 97
print.gazepoint_ml_split . . . 98
print.gazepoint_ml_split_validation . . . 99
restore_gazepoint_model_artifact . . . 101
select_gazepoint_model . . . 102
select_gazepoint_threshold . . . 103
simulate_gazepoint_governed_data . . . 104
simulate_gazepoint_research_handoffs . . . 105
split_gazepoint_ml_data . . . 105
summarize_gazepoint_resample_performance . . . 108
summarize_gazepoint_resample_uncertainty . . . 109
summarize_gazepoint_shift . . . 109
test_gazepoint_model_portability . . . 110
train_gazepoint_classifier . . . 111
tune_gazepoint_model . . . 112
validate_gazepoint_analysis_plan . . . 113
validate_gazepoint_conformal . . . 114
validate_gazepoint_decision_rule . . . 114
validate_gazepoint_environment . . . 115
validate_gazepoint_feature_manifest . . . 115
validate_gazepoint_fold_diagnostics . . . 116
validate_gazepoint_group_folds . . . 118
validate_gazepoint_handoff . . . 119
validate_gazepoint_ml_roles . . . 120
validate_gazepoint_ml_split . . . 122
validate_gazepoint_model_artifact . . . 123
validate_gazepoint_model_tuning . . . 124
validate_gazepoint_nested_evaluation . . . 124
validate_gazepoint_nested_folds . . . 125
validate_gazepoint_release_checksums . . . 125
validate_gazepoint_resample_evaluation . . . 126
validate_gazepoint_research_bundle . . . 126
validate_gazepoint_ro_crate . . . 127
validate_gazepoint_target_uncertainty . . . 127
validate_gazepoint_transportability . . . 128
validate_gp3ml_object_contract . . . 128

with_gazepoint_reproducible_output . . . 129
write_external_validation_report . . . 129
write_gazepoint_analysis_plan . . . 131
write_gazepoint_feature_manifest_csv . . . 131
write_gazepoint_fold_diagnostics_csv . . . 132
write_gazepoint_group_folds_csv . . . 134
write_gazepoint_ml_leakage_audit_csv . . . 137
write_gazepoint_ml_split_csv . . . 138
write_gazepoint_model_card . . . 140
write_gazepoint_model_tuning . . . 142
write_gazepoint_nested_evaluation . . . 143
write_gazepoint_release_checksums . . . 143
write_gazepoint_release_model_card . . . 144
write_gazepoint_reproducibility_audit . . . 144
write_gazepoint_reproducibility_report . . . 145
write_gazepoint_resample_evaluation . . . 146
write_gazepoint_ro_crate . . . 146
write_gazepoint_target_uncertainty . . . 147
write_gazepoint_transportability_report . . . 148
write_gp3ml_api_contracts . . . 149
write_gp3ml_governance_profile . . . 149

Index **151**

`apply_gazepoint_calibrator` *Apply a fitted probability calibrator*

Description

Apply a fitted probability calibrator

Usage

```
apply_gazepoint_calibrator(calibrator, probability)
```

Arguments

`calibrator`	A fitted `gp3ml_calibrator` object.
`probability`	Uncalibrated probabilities to transform.

Value

A numeric vector of calibrated probabilities, clipped to the open unit interval.

Examples

```
truth <- factor(
  rep(c("pass", "review"), 6),
  levels = c("pass", "review")
)
probability <- c(
  0.20, 0.70, 0.60, 0.55, 0.30, 0.80,
  0.65, 0.45, 0.40, 0.75, 0.50, 0.60
)
calibrator <- fit_gazepoint_calibrator(
  truth = truth,
  probability = probability,
  positive = "review"
)
apply_gazepoint_calibrator(
  calibrator,
  probability
)
```

---

apply_gazepoint_decision_rule

Apply a governed classification decision rule

Description

Apply a governed classification decision rule

Usage

```
apply_gazepoint_decision_rule(
  rule,
  probability,
  positive,
  negative,
  abstain_label = ".abstain"
)
```

Arguments

rule	A validated decision rule.
probability	Positive-class probability.
positive	Positive class label.
negative	Negative class label.
abstain_label	Label used for abstentions.

Value

A factor of governed decisions.

assert_gp3ml_engine_available *Assert that a gp3ml engine is available*

Description

Assert that a gp3ml engine is available

Usage

```
assert_gp3ml_engine_available(engine, check_keras_backend = FALSE)
```

Arguments

engine	Engine name.
check_keras_backend	Whether to verify a configured Keras backend.

Value

Invisibly TRUE on success.

assert_gp3ml_use_case *Assert that a task is within the permitted gp3ml scope*

Description

Assert that a task is within the permitted gp3ml scope

Usage

```
assert_gp3ml_use_case(task, data = NULL)
```

Arguments

task	A gp3ml_task object.
data	Optional data frame used to validate task columns.

Value

Invisibly returns TRUE when the task is permitted; otherwise, the function stops with an error.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = example_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
assert_gp3ml_use_case(task, example_data)
```

---

assess_gazepoint_calibration

Calibration assessment with bootstrap uncertainty

Description

Calibration assessment with bootstrap uncertainty

Usage

```
assess_gazepoint_calibration(
  truth,
  probability,
  positive = NULL,
  bins = 10L,
  bootstrap = 200L,
  conf_level = 0.95,
```

```
  seed = 1L
)
```

Arguments

truth	Observed binary outcome values.
probability	Predicted positive-class probabilities.
positive	Label representing the positive class.
bins	Number of reliability bins.
bootstrap	Number of bootstrap replicates.
conf_level	Confidence level for percentile intervals.
seed	Deterministic random seed.

Value

A gp3ml_calibration_assessment object containing calibration summaries, reliability-bin results, bootstrap intervals, and assessment settings.

Examples

```
truth <- factor(
  rep(rep(c("pass", "review"), 5), 10),
  levels = c("pass", "review")
)
probability <- rep(
  seq(0.10, 0.90, length.out = 10),
  each = 10
)

assessment <- assess_gazepoint_calibration(
  truth = truth,
  probability = probability,
  positive = "review",
  bins = 5L,
  bootstrap = 10L,
  seed = 101L
)
assessment
```

---

assess_gazepoint_conformal_coverage

Assess conformal coverage

Description

Assess conformal coverage

Usage

```
assess_gazepoint_conformal_coverage(
  object,
  truth,
  interval = NULL,
  set = NULL,
  unit = NULL
)
```

Arguments

object	A gp3ml_conformal_fit.
truth	Observed outcomes.
interval	Regression interval data frame.
set	Classification set data frame.
unit	Optional assessment-unit identifier.

Value

A gp3ml_conformal_coverage.

---

as_gp3ml_data *Extract model-ready data from a gp3ml handoff object*

Description

Extract model-ready data from a gp3ml handoff object

Usage

```
as_gp3ml_data(x, ...)
```

Arguments

x	A gp3ml_handoff or gp3ml_handoff_bundle.
...	Reserved for future adapters.

Value

A data frame.

audit_gazepoint_abstention *Audit abstention decisions*

Description

Audit abstention decisions

Usage

```
audit_gazepoint_abstention(truth, decision, abstain_label = ".abstain")
```

Arguments

truth	Observed binary outcome.
decision	Decisions returned by apply_gazepoint_decision_rule().
abstain_label	Abstention label.

Value

A gp3ml_abstention_audit.

audit_gazepoint_dataset_shift *Audit predictor distribution shift*

Description

Audit predictor distribution shift

Usage

```
audit_gazepoint_dataset_shift(
  development,
  external,
  predictors = intersect(names(development), names(external)),
  thresholds = list(smd_review = 0.2, smd_fail = 0.5, outside_review = 0.05, outside_fail
    = 0.2, tv_review = 0.2, tv_fail = 0.4)
)
```

Arguments

development	Development/training data.
external	Independent or later data to compare.
predictors	Predictors to audit. Defaults to common columns.
thresholds	Named threshold list.

Value

A gp3ml_dataset_shift_audit.

---

audit_gazepoint_group_folds *Aggregate leakage audits across group-aware folds*

Description

Aggregate leakage audits across group-aware folds

Usage

```
audit_gazepoint_group_folds(x)
```

Arguments

x	A gazepoint_group_folds object.

Value

An object of class gazepoint_group_folds_audit.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
```

```
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
audit <- audit_gazepoint_group_folds(folds)
audit
```

`audit_gazepoint_missingness_shift` *Audit missingness shift*

Description

Audit missingness shift

Usage

```
audit_gazepoint_missingness_shift(
  development,
  external,
  predictors = intersect(names(development), names(external)),
  review_delta = 0.1,
  fail_delta = 0.25
)
```

Arguments

development	Development data.
external	External/new data.
predictors	Predictors to audit.
review_delta	Review threshold for absolute missingness change.
fail_delta	Fail threshold for absolute missingness change.

Value

A gp3ml_missingness_shift_audit.

---

audit_gazepoint_ml_leakage

Audit leakage between predictive-analysis partitions

Description

Audits already-defined analysis and assessment partitions for common forms of leakage and for incompatibility with a declared generalization target. The function does not create data splits, preprocess variables, select features, or fit predictive models.

Usage

```
audit_gazepoint_ml_leakage(
  analysis,
  assessment,
  outcome,
  predictors,
  participant_id = NULL,
  trial_id = NULL,
  stimulus_id = NULL,
  generalization_target = c("new_trials_known_participants", "new_participants",
    "new_stimuli", "new_participants_and_new_stimuli"),
  target_derived = character(),
  post_outcome = character()
)
```

Arguments

analysis	A data frame containing the analysis or training partition.
assessment	A data frame containing the assessment or test partition.
outcome	A single column name identifying the outcome.
predictors	A character vector identifying intended predictor columns.
participant_id	An optional participant-identifier column.
trial_id	An optional trial-identifier column.
stimulus_id	An optional stimulus-identifier column.
generalization_target	The predictive generalization target. One of "new_trials_known_participants", "new_participants", "new_stimuli", or "new_participants_and_new_stimuli".
target_derived	Character vector of columns known to have been derived directly from the outcome.
post_outcome	Character vector of columns measured or constructed after the outcome became available.

Details

The overall status is "fail" when at least one failing check is present, "review" when no failing checks are present but at least one review item is present, and "pass" otherwise.

When participant_id is supplied, trial overlap is evaluated using composite participant-trial units. This permits trial labels such as "T01" to be reused by different participants without being treated as leakage. Without participant_id, trial_id is assumed to be globally unique.

The audit can identify structural leakage visible in the supplied partitions and declared variable roles. It cannot prove that preprocessing or feature selection was estimated inside resampling folds. Those operations require separate provenance and resampling safeguards.

The function does not determine whether an outcome is scientifically or ethically appropriate. All uses remain subject to the package governance and prohibited-use statements.

Value

An object of class gazepoint_ml_leakage_audit. The object contains an overall status, partition summary, complete check table, and machine-readable table of non-passing issues.

Examples

```
analysis <- data.frame(
  participant_id = c("P01", "P01", "P02", "P02"),
  trial_id = c("T01", "T02", "T03", "T04"),
  stimulus_id = c("S01", "S02", "S03", "S04"),
  outcome = c(0, 1, 0, 1),
  fixation_duration = c(210, 240, 225, 260),
  pupil_change = c(0.10, 0.16, 0.12, 0.18)
)

assessment <- data.frame(
```

```
  participant_id = c("P03", "P03", "P04", "P04"),
  trial_id = c("T05", "T06", "T07", "T08"),
  stimulus_id = c("S05", "S06", "S07", "S08"),
  outcome = c(1, 0, 1, 0),
  fixation_duration = c(275, 230, 290, 245),
  pupil_change = c(0.21, 0.11, 0.24, 0.14)
)

audit_gazepoint_ml_leakage(
  analysis = analysis,
  assessment = assessment,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants"
)
```

`audit_gazepoint_model_robustness` *Audit multiple robustness dimensions*

Description

Audit multiple robustness dimensions

Usage

```
audit_gazepoint_model_robustness(
  seed_stability = NULL,
  feature_stability = NULL,
  threshold_stability = NULL,
  missingness_stability = NULL,
  relative_sd_review = 0.05,
  relative_sd_fail = 0.15
)
```

Arguments

`seed_stability`	Optional seed-stability object.
`feature_stability`	Optional feature-stability object.
`threshold_stability`	Optional threshold-stability object.
`missingness_stability`	Optional missingness-stability object.

relative_sd_review
: Relative SD threshold for review.

relative_sd_fail
: Relative SD threshold for fail.

Value

A gp3ml_model_robustness_audit.

---

audit_gazepoint_nested_resampling

Audit nested grouped resampling for outer-assessment leakage

Description

Audit nested grouped resampling for outer-assessment leakage

Usage

```
audit_gazepoint_nested_resampling(x)

## S3 method for class 'gp3ml_nested_resampling_audit'
print(x, ...)
```

Arguments

x	A gp3ml_nested_folds object.
...	Additional arguments passed to the print method.

Value

A gp3ml_nested_resampling_audit.

---

audit_gazepoint_plan_deviations

Audit deviations from a locked analysis plan

Description

Audit deviations from a locked analysis plan

Usage

```
audit_gazepoint_plan_deviations(
  plan,
  actual,
  fields = c("outcome", "predictors", "generalization_target", "primary_metric",
   "secondary_metrics", "calibration_metric", "uncertainty_method", "threshold_policy",
    "candidate_models", "preprocessing_plan")
)
```

Arguments

plan	A locked analysis plan.
actual	Named list describing the analysis actually performed.
fields	Fields to compare.

Value

A gp3ml_plan_deviation_audit.

---

audit_gazepoint_reproducibility

Audit generated artifacts for volatile output

Description

Audit generated artifacts for volatile output

Usage

```
audit_gazepoint_reproducibility(
  paths,
  recursive = TRUE,
 extensions = c("R", "Rmd", "Rd", "md", "txt", "html", "json", "csv", "yml", "yaml")
)
```

Arguments

paths	Files or directories to audit.
recursive	Whether directories are searched recursively.
extensions	Text-file extensions to inspect.

Value

A gp3ml_reproducibility_audit.

audit_gp3ml_api_stability *Audit gp3ml API stability*

Description

Audit gp3ml API stability

Usage

```
audit_gp3ml_api_stability(registry = gp3ml_api_contracts())
```

Arguments

registry	Contract registry.

Value

A gp3ml_api_stability_audit object.

audit_gp3ml_governance_profile *Audit a governance-evidence profile*

Description

Audit a governance-evidence profile

Usage

```
audit_gp3ml_governance_profile(profile)
```

Arguments

profile	Governance profile.

Value

A gp3ml_governance_profile_audit.

`bake_gazepoint_preprocessor` *Apply a fitted preprocessing engine*

Description

Apply a fitted preprocessing engine

Usage

```
bake_gazepoint_preprocessor(preprocessor, new_data)
```

Arguments

`preprocessor`	A fitted `gp3ml_preprocessor` object.
`new_data`	Data to transform using the fitted parameters.

Value

A numeric model matrix transformed using only the parameters stored in the fitted preprocessor.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
preprocessor <- fit_gazepoint_preprocessor(
  data = example_data,
  predictors = c(
    "fixation_duration",
    "pupil_change",
    "condition"
  )
)
```

```
baked <- bake_gazepoint_preprocessor(
  preprocessor,
  example_data
)
dim(baked)
```

`bootstrap_gazepoint_metrics` *Bootstrap uncertainty intervals for performance metrics*

Description

Bootstrap uncertainty intervals for performance metrics

Usage

```
bootstrap_gazepoint_metrics(
  task,
  truth,
  prediction = NULL,
  probability = NULL,
  threshold = 0.5,
  bootstrap = 1000L,
  conf_level = 0.95,
  seed = 1L
)
```

Arguments

`task`	A governed `gp3ml_task` object.
`truth`	Observed outcome values.
`prediction`	Predicted classes or numeric values.
`probability`	Predicted positive-class probabilities.
`threshold`	Probability threshold for classification.
`bootstrap`	Number of bootstrap replicates.
`conf_level`	Confidence level for percentile intervals.
`seed`	Deterministic random seed.

Value

A `gp3ml_metric_uncertainty` object containing point estimates, percentile intervals, bootstrap draws, resampling settings, and the governed task.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = example_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
probability <- seq(
  0.20,
  0.80,
  length.out = nrow(example_data)
)
predicted <- factor(
  ifelse(probability >= 0.5, "review", "pass"),
  levels = levels(example_data$quality_status)
)
uncertainty <- bootstrap_gazepoint_metrics(
  task = task,
  truth = example_data$quality_status,
  prediction = predicted,
  probability = probability,
  bootstrap = 10L,
  seed = 101L
)
uncertainty
```

`bootstrap_gazepoint_metrics_by_unit` *Generalization-target-aligned bootstrap uncertainty*

Description

Resamples observations or declared clusters while preserving every row that belongs to a sampled cluster. Repeated cluster draws duplicate all associated rows. The returned object records the resampling unit and must not be described as uncertainty for another unit.

Usage

```
bootstrap_gazepoint_metrics_by_unit(
  task,
  truth,
  prediction = NULL,
  probability = NULL,
  participant_id = NULL,
  stimulus_id = NULL,
 unit = c("observation", "participant", "stimulus", "participant_and_stimulus"),
  bootstrap = 1000L,
  conf_level = 0.95,
  seed = 1L,
  threshold = 0.5,
  stratify_observations = TRUE
)

## S3 method for class 'gp3ml_target_uncertainty'
print(x, ...)
```

Arguments

`task`	Governed task.
`truth`	Observed outcomes.
`prediction`	Predicted classes or numeric outcomes.
`probability`	Positive-class probabilities.
`participant_id`	Participant identifiers for participant-based methods.
`stimulus_id`	Stimulus identifiers for stimulus-based methods.
`unit`	Resampling unit.
`bootstrap`	Number of replicates.
`conf_level`	Percentile interval level.
`seed`	Deterministic seed.
`threshold`	Classification threshold.
`stratify_observations`	Whether the observation-level classification bootstrap preserves class counts.

x	An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.
...	Additional arguments passed to the print method.

Value

A gp3ml_target_uncertainty object.

Examples

```
data <- simulate_gazepoint_governed_data(12L, 4L, 1L, 404L)
task <- create_gazepoint_synthetic_task(data, "recording_quality", "new_participants")
probability <- seq(0.15, 0.85, length.out = nrow(data))
prediction <- factor(
  ifelse(probability >= 0.5, "review", "pass"),
  levels = levels(data$quality_status)
)
uncertainty <- bootstrap_gazepoint_metrics_by_unit(
  task,
  truth = data$quality_status,
  prediction = prediction,
  probability = probability,
  participant_id = data$participant_id,
  unit = "participant",
  bootstrap = 20L,
  seed = 404L
)
uncertainty
```

---

capture_gazepoint_environment

Capture a reproducibility environment record

Description

Capture a reproducibility environment record

Usage

```
capture_gazepoint_environment(
  packages = unique(c("gp3ml", loadedNamespaces())),
  root = ".",
  include_renv = FALSE
)
```

Arguments

packages	Packages to record. Defaults to gp3ml and currently loaded namespaces.
root	Repository/project root used to capture Git SHA.
include_renv	Whether to record an existing renv.lock hash.

Value

A gp3ml_environment_record.

---

collect_gazepoint_fold_predictions

Collect predictions from a grouped-fold evaluation

Description

Collect predictions from a grouped-fold evaluation

Usage

```
collect_gazepoint_fold_predictions(x, include_failed = TRUE)
```

Arguments

x	A gp3ml_resample_evaluation.
include_failed	Whether failed folds are represented by explicit status rows when they produced no predictions.

Value

A data frame of row-level assessment predictions with fold labels.

---

combine_gazepoint_handoffs

Combine validated cross-package handoffs

Description

Combine validated cross-package handoffs

Usage

```
combine_gazepoint_handoffs(
  handoffs,
  keys = NULL,
  collision = c("error", "prefix")
)
```

Arguments

handoffs	Named list of gp3ml_handoff objects.
keys	Optional join keys; defaults to the first handoff's keys.
collision	How to handle overlapping non-key column names.

Value

A gp3ml_handoff_bundle.

---

compare_gazepoint_environments

Compare two environment records

Description

Compare two environment records

Usage

```
compare_gazepoint_environments(reference, current)
```

Arguments

reference	Reference environment.
current	Current environment.

Value

A gp3ml_environment_comparison.

---

compare_gazepoint_models

Compare governed model candidates without selecting a winner

Description

Compare governed model candidates without selecting a winner

Usage

```
compare_gazepoint_models(x, metrics = NULL)
```

Arguments

x	A gp3ml_model_tuning object.
metrics	Optional metric names.

Value

A data frame retaining candidate status, failures, complexity, interpretability, and fold-distribution summaries.

`create_external_validation_report` *Create an external-validation report object*

Description

Create an external-validation report object

Usage

```
create_external_validation_report(
  validation,
  development_metrics = NULL,
  limitations = character()
)
```

Arguments

`validation`	A `gp3ml_external_validation` object.
`development_metrics`	Optional development-sample metrics.
`limitations`	Character vector describing report limitations.

Value

A `gp3ml_external_validation_report` object containing the validation result, optional development metrics, limitations, and prohibited-use information.

Examples

```
training_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
training_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
```

```
  data = training_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
model <- train_gazepoint_classifier(
  data = training_data,
  task = task,
  predictors = c("fixation_duration", "pupil_change"),
  engine = "glm",
  seed = 101L
)
external_data <- training_data
external_data$participant_id <- rep(
  sprintf("E%02d", 1:12),
  each = 2
)
external_data$trial_id <- sprintf("ET%02d", 1:24)
external_data$fixation_duration <-
  external_data$fixation_duration + 4
external_data$pupil_change <- cos(seq_len(24) / 4)
validation <- evaluate_external_validation(
  model = model,
  external_data = external_data,
  label = "synthetic_external",
  bootstrap = 10L,
  seed = 101L
)
report <- create_external_validation_report(
  validation = validation,
  limitations = "Synthetic external-validation example."
)
report
```

`create_gazepoint_decision_rule` *Create a governed classification decision rule*

Description

Create a governed classification decision rule

Usage

```
create_gazepoint_decision_rule(
```

```
  metric,
  direction = c("maximize", "minimize"),
  threshold = NULL,
  threshold_origin = c("predeclared", "training", "inner_resampling"),
  cost_false_positive = 1,
  cost_false_negative = 1,
  abstention_allowed = FALSE,
  abstention_interval = NULL,
  calibration_source = "none",
  training_partition = "analysis",
  generalization_target,
  scientific_justification
)
```

Arguments

`metric`	Metric used to justify the threshold.
`direction`	Either `"maximize"` or `"minimize"`.
`threshold`	Optional probability threshold. Leave `NULL` until selected.
`threshold_origin`	Origin of the threshold.
`cost_false_positive`	Non-negative false-positive cost.
`cost_false_negative`	Non-negative false-negative cost.
`abstention_allowed`	Whether abstention is permitted.
`abstention_interval`	Optional length-two probability interval. Probabilities inside the interval are labelled as abstentions.
`calibration_source`	Description of the calibration source.
`training_partition`	Description of the data partition used to determine the threshold.
`generalization_target`	Declared generalization target.
`scientific_justification`	Explicit scientific justification.

Value

A `gp3ml_decision_rule`.

`create_gazepoint_feature_manifest` *Create a Gazepoint feature-provenance manifest*

Description

Creates a structured provenance manifest for intended predictive features. Each row records where a feature originated, when it became available, whether it is outcome-derived or post-outcome, and where any data-dependent preprocessing was estimated.

Usage

```
create_gazepoint_feature_manifest(
  features,
  scientific_source = NA_character_,
  source_table = NA_character_,
  transformation = "none",
  availability_stage = "unknown",
  prediction_time_available = NA,
  outcome_derived = FALSE,
  post_outcome = FALSE,
  identifier = FALSE,
  preprocessing_scope = "unknown",
  fold_local_required = NA,
  reviewer_notes = ""
)
```

Arguments

`features`	Character vector of unique feature names.
`scientific_source`	Scientific or measurement source for each feature.
`source_table`	Source export, table, or object for each feature.
`transformation`	Description of the transformation used to construct each feature.
`availability_stage`	Availability stage for each feature. One of `"pre_exposure"`, `"during_exposure"`, `"post_exposure_pre_outcome"`, `"at_prediction"`, `"post_outcome"`, or `"unknown"`.
`prediction_time_available`	Logical vector indicating whether each feature is available at the intended prediction time.
`outcome_derived`	Logical vector indicating whether each feature was derived directly or indirectly from the outcome.
`post_outcome`	Logical vector indicating whether each feature was measured or constructed after the outcome became available.

`identifier` Logical vector indicating whether each feature is an identifier or row-location variable.

`preprocessing_scope`
Scope in which any data-dependent preprocessing was estimated. One of `"none"`, `"global"`, `"analysis_partition"`, `"resampling_fold"`, or `"unknown"`.

`fold_local_required`
Logical vector indicating whether preprocessing for each feature must be estimated separately inside each resampling fold.

`reviewer_notes` Optional reviewer-facing notes.

Details

Each row is treated as an intended predictor. Consequently, outcome-derived, post-outcome, unavailable, and identifier features are treated as failing conditions by `validate_gazepoint_feature_manifest()`.

The manifest records declared provenance. It does not independently prove that preprocessing was estimated within the stated scope.

Value

A data frame of class `gazepoint_feature_manifest`.

Examples

```
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint all-gaze export"
  ),
  source_table = c("fixations", "all_gaze"),
  transformation = c(
    "Trial-level mean",
    "Baseline-adjusted change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = c("none", "resampling_fold"),
  fold_local_required = c(FALSE, TRUE)
)

manifest
```

---

create_gazepoint_group_folds

Create deterministic group-aware Gazepoint resampling folds

Description

Creates repeated grouped assessment folds that preserve the grouping structure implied by an explicit generalization target. A passing feature-provenance manifest is required, and every analysis-assessment pair is evaluated using the leakage audit.

Usage

```
create_gazepoint_group_folds(
  data,
  outcome,
  predictors,
  feature_manifest,
  generalization_target,
  participant_id = NULL,
  trial_id = NULL,
  stimulus_id = NULL,
  v = 5L,
  repeats = 1L,
  seed = 1L,
  source_row_id = ".gp3ml_source_row"
)
```

Arguments

`data`	A data frame containing the outcome, predictors, and grouping identifiers.
`outcome`	Name of the outcome column.
`predictors`	Character vector naming intended predictors.
`feature_manifest`	A feature manifest containing all intended predictors.
`generalization_target`	One of `"new_trials_known_participants"`, `"new_participants"`, `"new_stimuli"`, or `"new_participants_and_new_stimuli"`.
`participant_id`	Optional participant-identifier column.
`trial_id`	Optional trial-identifier column.
`stimulus_id`	Optional stimulus-identifier column.
`v`	Number of group folds. For simultaneous participant and stimulus generalization, a length-two vector specifies participant and stimulus fold counts.
`repeats`	Number of repeated fold assignments.
`seed`	Integer random seed. The caller's random-number state is restored.
`source_row_id`	Name of the source-row identifier added to returned partitions.

Details

For new trials among known participants, participant-trial units are assigned separately within each participant. For simultaneous participant and stimulus generalization, crossed participant-stimulus

assessment blocks are created; cross-block rows are excluded from that fold. Each source row appears in assessment exactly once per repeat.

This function does not perform preprocessing, feature selection, tuning, nested resampling, or model fitting.

Value

An object of class `gazepoint_group_folds`.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
```

```
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
folds
```

`create_gazepoint_handoff` *Create a lightweight cross-package Gazepoint handoff*

Description

Create a lightweight cross-package Gazepoint handoff

Usage

```
create_gazepoint_handoff(
  data,
  source_package,
  source_version = NULL,
  producer = NULL,
  keys,
  outcome = NULL,
  predictors = character(),
  feature_manifest = NULL,
  notes = character()
)
```

Arguments

`data`	Prepared data frame.
`source_package`	Upstream source package or `study_design/custom`.

source_version	Optional source-package version.
producer	Optional upstream function/workflow label.
keys	Character vector of row-identifying join keys.
outcome	Optional observed outcome column.
predictors	Optional prepared predictor columns.
feature_manifest	Optional gp3ml feature-provenance manifest.
notes	Optional handoff notes.

Value

A gp3ml_handoff object.

`create_gazepoint_model_artifact` *Create a portable governed model artifact*

Description

Create a portable governed model artifact

Usage

```
create_gazepoint_model_artifact(
  model,
  preprocessor = model$preprocessor %||% NULL,
  feature_manifest = NULL,
  task = model$task %||% NULL,
  decision_rule = NULL,
  model_card = NULL,
  reference_data = NULL,
  bundle_model = TRUE
)
```

Arguments

model	A fitted gp3ml_model or controlled model object.
preprocessor	Optional preprocessing object.
feature_manifest	Optional feature manifest.
task	Optional task; defaults to model$task.
decision_rule	Optional decision rule.
model_card	Optional model card.
reference_data	Optional deterministic prediction fixture.
bundle_model	Whether to attempt bundle::bundle() when available.

Value

A gp3ml_model_artifact.

`create_gazepoint_model_card` *Create a governance-focused model card*

Description

Create a governance-focused model card

Usage

```
create_gazepoint_model_card(
  model,
  intended_use,
  evaluation = NULL,
  calibration = NULL,
  feature_manifest = NULL,
  external_validation = NULL,
  limitations = character(),
  ethical_review = NULL
)
```

Arguments

model	A fitted gp3ml_model object.
intended_use	Explicit description of the intended research use.
evaluation	Optional performance-evaluation object.
calibration	Optional calibration-assessment object.
feature_manifest	Optional feature-provenance manifest.
external_validation	Optional external-validation result.
limitations	Character vector describing model limitations.
ethical_review	Optional ethical-review information.

Value

A gp3ml_model_card object containing task, model, governance, evaluation, calibration, provenance, external-validation, and limitation metadata.

Examples

```
training_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
training_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = training_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
model <- train_gazepoint_classifier(
  data = training_data,
  task = task,
  predictors = c("fixation_duration", "pupil_change"),
  engine = "glm",
  seed = 101L
)
card <- create_gazepoint_model_card(
  model = model,
  intended_use = paste(
    "Support manual review of predefined",
    "recording-quality status"
  ),
  limitations = "Synthetic example for documentation."
)
card
```

`create_gazepoint_nested_folds` *Create nested grouped resampling from mature outer folds*

Description

Inner folds are constructed only from each outer analysis partition and preserve the declared participant/stimulus generalization target. The outer assessment partition is never used for inner preprocessing or tuning.

Usage

```
create_gazepoint_nested_folds(
  outer_folds,
  inner_v = 3L,
  inner_repeats = 1L,
  seed = 1L,
  continue_on_error = FALSE
)

## S3 method for class 'gp3ml_nested_folds'
print(x, ...)
```

Arguments

outer_folds	A validated gazepoint_group_folds object.
inner_v	Number of inner folds.
inner_repeats	Number of inner repeats.
seed	Base deterministic seed.
continue_on_error	Whether infeasible outer folds are retained as failures instead of stopping immediately.
x	An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.
...	Additional arguments passed to the print method.

Value

A gp3ml_nested_folds object.

Examples

```
data <- simulate_gazepoint_governed_data(16L, 4L, 1L, 303L)
predictors <- c("tracking_ratio", "blink_rate", "gaze_dispersion")
manifest <- create_gazepoint_synthetic_manifest("quality_status", predictors)
outer <- create_gazepoint_group_folds(
  data, "quality_status", predictors, manifest,
  "new_participants", "participant_id", "trial_id", "stimulus_id",
  v = 4L, repeats = 1L, seed = 303L
)
nested <- create_gazepoint_nested_folds(
  outer,
  inner_v = 3L,
```

```
  inner_repeats = 1L,
  seed = 303L
)
nested
```

---

create_gazepoint_release_evidence
Create a release evidence manifest

Description

Create a release evidence manifest

Usage

```
create_gazepoint_release_evidence(
  objects = list(),
  files = character(),
  version = "0.2.0",
  notes = character()
)

## S3 method for class 'gp3ml_release_evidence'
print(x, ...)
```

Arguments

objects	Named analysis objects to fingerprint.
files	Named file paths to checksum.
version	Intended future release version.
notes	Optional release notes.
x	An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.
...	Additional arguments passed to the print method.

Value

A gp3ml_release_evidence object.

`create_gazepoint_release_model_card` *Create a release-ready governed model card*

Description

Extends the existing model-card structure with explicit model-selection, target-aligned uncertainty, nested-resampling, and transportability fields.

Usage

```
create_gazepoint_release_model_card(
  model,
  intended_use,
  evaluation = NULL,
  selection = NULL,
  uncertainty = NULL,
  calibration = NULL,
  feature_manifest = NULL,
  transportability = NULL,
  limitations,
  ethical_review = NULL,
  deployment_status = "research_review_only"
)

## S3 method for class 'gp3ml_release_model_card'
print(x, ...)
```

Arguments

`model`	Fitted governed model.
`intended_use`	Intended scientific use.
`evaluation`	Grouped or nested evaluation.
`selection`	Optional `gp3ml_model_selection`.
`uncertainty`	Optional target-aligned uncertainty object.
`calibration`	Optional calibration assessment.
`feature_manifest`	Optional feature manifest.
`transportability`	Optional transportability report.
`limitations`	Required limitations.
`ethical_review`	Optional ethical-review information.
`deployment_status`	Deployment status; defaults to research review only.

x	An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.
...	Additional arguments passed to the print method.

Value

A gp3ml_release_model_card.

`create_gazepoint_reproducibility_report` *Create a reproducibility report*

Description

Create a reproducibility report

Usage

```
create_gazepoint_reproducibility_report(
  objects = list(),
  data = NULL,
  seeds = list(),
  notes = character(),
  project_path = getwd()
)
```

Arguments

objects	Named objects to fingerprint.
data	Optional data frame to fingerprint.
seeds	Named list of deterministic seeds.
notes	Optional reproducibility notes.
project_path	Project directory recorded in the report.

Value

A gp3ml_reproducibility_report object containing runtime information, object and data fingerprints, seeds, Git metadata, notes, and prohibited uses.

Examples

```
example_data <- data.frame(
  trial_id = sprintf("T%02d", 1:6),
  fixation_duration = c(190, 205, 198, 214, 202, 220),
  stringsAsFactors = FALSE
)
report <- create_gazepoint_reproducibility_report(
  objects = list(
    fixation_values = example_data$fixation_duration
  ),
  data = example_data,
  seeds = list(example = 101L),
  notes = "Synthetic documentation example.",
  project_path = tempdir()
)
report
```

---

create_gazepoint_synthetic_manifest

Create a synthetic governed feature manifest

Description

Create a synthetic governed feature manifest

Usage

```
create_gazepoint_synthetic_manifest(
  outcome,
  predictors,
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  trial_id = "trial_id"
)
```

Arguments

`outcome`	Name of the observed synthetic outcome.
`predictors`	Predictor names to declare.
`participant_id`	Participant identifier column.
`stimulus_id`	Stimulus identifier column.
`trial_id`	Trial identifier column.

Value

A `gazepoint_feature_manifest` produced by `create_gazepoint_feature_manifest()`.

Examples

```
create_gazepoint_synthetic_manifest(
  outcome = "quality_status",
  predictors = c("tracking_ratio", "blink_rate", "gaze_dispersion")
)
```

`create_gazepoint_synthetic_task` *Create one of the governed synthetic demonstration tasks*

Description

Create one of the governed synthetic demonstration tasks

Usage

```
create_gazepoint_synthetic_task(
  data,
  workflow = c("recording_quality", "assigned_condition", "observed_behavior",
    "observed_duration"),
  generalization_target = c("new_trials_known_participants", "new_participants",
    "new_stimuli", "new_participants_and_new_stimuli")
)
```

Arguments

`data`	Synthetic data from `simulate_gazepoint_governed_data()`.
`workflow`	Workflow name.
`generalization_target`	Declared generalization target.

Value

A governed `gp3ml_task`.

Examples

```
synthetic <- simulate_gazepoint_governed_data(12L, 4L, 1L, 101L)
create_gazepoint_synthetic_task(
  synthetic,
  workflow = "recording_quality",
  generalization_target = "new_participants"
)
```

`create_gazepoint_tuning_grid` *Create an explicit governed tuning grid*

Description

Candidate values are fully materialized before evaluation. No hidden metric, default ranking rule, or automatic winner is created.

Usage

```
create_gazepoint_tuning_grid(
  engine,
  engine_grid = list(),
  preprocessor_grid = list(),
  thresholds = 0.5,
  complexity = NA,
  interpretability = NA,
  labels = NULL
)

## S3 method for class 'gp3ml_tuning_grid'
print(x, ...)
```

Arguments

`engine`	One or more governed engine names.
`engine_grid`	Named list of engine-argument candidate values.
`preprocessor_grid`	Named list of preprocessing-argument candidate values.
`thresholds`	One or more explicit classification thresholds.
`complexity`	Optional complexity labels or numeric scores.
`interpretability`	Optional interpretability labels or numeric scores.
`labels`	Optional candidate labels.
`x`	An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.
`...`	Additional arguments passed to the print method.

Value

A `gp3ml_tuning_grid` with one row per explicit candidate.

Examples

```
grid <- create_gazepoint_tuning_grid(
  engine = "glm",
  preprocessor_grid = list(center = c(TRUE, FALSE), scale = TRUE),
  thresholds = c(0.4, 0.5),
  complexity = "low",
  interpretability = "high"
)
grid
```

`create_gp3ml_governance_profile`
Create a governance-evidence profile

Description

Create a governance-evidence profile

Usage

```
create_gp3ml_governance_profile(
  evidence,
  framework = c("gp3ml-native", "NIST-AI-RMF-1.0", "ISO-23894-oriented",
    "ISO-42001-oriented")
)
```

Arguments

`evidence`	Named list of gp3ml evidence objects.
`framework`	Governance crosswalk.

Value

A `gp3ml_governance_profile`.

`declare_gazepoint_analysis_plan`
Declare a frozen-analysis-plan contract

Description

Declare a frozen-analysis-plan contract

Usage

```
declare_gazepoint_analysis_plan(
  research_question,
  scientific_purpose,
  outcome,
  outcome_definition,
  predictors,
  generalization_target,
  grouping_variables = character(),
  eligible_population,
  exclusion_rules = character(),
  preprocessing_plan,
  candidate_models,
  primary_metric,
  secondary_metrics = character(),
  calibration_metric = NULL,
  uncertainty_method,
  threshold_policy = NULL,
  external_validation_required = FALSE,
  seed_strategy,
  prohibited_interpretations = gp3ml_prohibited_uses()
)
```

Arguments

research_question	Research question.
scientific_purpose	Explicit scientific purpose.
outcome	Outcome name.
outcome_definition	Operational definition of the observed outcome.
predictors	Predeclared predictors.
generalization_target	Intended generalization target.
grouping_variables	Grouping columns.
eligible_population	Eligibility statement.
exclusion_rules	Character vector of predeclared exclusions.
preprocessing_plan	Preprocessing plan.
candidate_models	Candidate model specifications or names.
primary_metric	Primary metric.

`secondary_metrics`
: Secondary metrics.

`calibration_metric`
: Calibration metric.

`uncertainty_method`
: Uncertainty method.

`threshold_policy`
: Threshold/decision policy.

`external_validation_required`
: Whether independent validation is required.

`seed_strategy`
: Deterministic seed strategy.

`prohibited_interpretations`
: Character vector of prohibited interpretations.

Value

A mutable `gp3ml_analysis_plan` until locked.

`declare_gazepoint_external_dataset` *Declare an external dataset and its independence status*

Description

Declare an external dataset and its independence status

Usage

```
declare_gazepoint_external_dataset(
  data,
  label,
  independent,
  origin,
  collection_period = NULL,
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  notes = character()
)

## S3 method for class 'gp3ml_external_dataset_declaration'
print(x, ...)
```

Arguments

data	Candidate external-validation data.
label	Dataset label.
independent	Explicit logical declaration of independence from model development and internal resampling.
origin	Human-readable origin or collection source.
collection_period	Optional collection period.
participant_id	Participant identifier column.
stimulus_id	Stimulus identifier column.
notes	Optional notes.
x	An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.
...	Additional arguments passed to the print method.

Value

A gp3ml_external_dataset_declaration.

Examples

```
external <- simulate_gazepoint_governed_data(8L, 4L, 1L, 505L)
declaration <- declare_gazepoint_external_dataset(
  external,
  label = "synthetic_external_site",
  independent = TRUE,
  origin = "Independent deterministic synthetic site"
)
declaration
```

---

declare_gazepoint_task

Declare a governed Gazepoint prediction task

Description

Declare a governed Gazepoint prediction task

Usage

```
declare_gazepoint_task(
  data,
  outcome,
  purpose,
  task_type = c("classification", "regression"),
  unit_id,
  participant_id = NULL,
  stimulus_id = NULL,
  generalization_target = c("new_trials_known_participants", "new_participants",
    "new_stimuli", "new_participants_and_new_stimuli", "external_validation"),
  positive = NULL,
  observed_outcome = TRUE,
  sensitive_outcome = FALSE
)
```

Arguments

`data`	A data frame containing the outcome and task identifiers.
`outcome`	Name of the explicitly observed outcome column.
`purpose`	One explicit scientific-purpose statement.
`task_type`	Either `classification` or `regression`.
`unit_id`	Column identifying the prediction unit.
`participant_id`	Optional participant-identifier column.
`stimulus_id`	Optional stimulus-identifier column.
`generalization_target`	The intended target of generalization.
`positive`	Positive outcome level for binary classification.
`observed_outcome`	Whether the outcome was directly observed.
`sensitive_outcome`	Whether the outcome is sensitive or prohibited.

Value

A governed `gp3ml_task` object describing the outcome, scientific purpose, prediction unit, grouping roles, task type, and generalization target.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
```

```
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = example_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
task
```

`diagnose_gazepoint_group_folds` *Diagnose group-aware Gazepoint resampling folds*

Description

Creates fold-size, repeat-level, grouping, assessment-coverage, outcome-balance, and exclusion diagnostics for an existing `gazepoint_group_folds` object.

Usage

```
diagnose_gazepoint_group_folds(x, imbalance_review = 1.5, imbalance_fail = 2)
```

Arguments

`x`	A `gazepoint_group_folds` object.
`imbalance_review`	Fold-size ratio above which diagnostics receive a `review` status.
`imbalance_fail`	Fold-size ratio above which diagnostics receive a `fail` status.

Value

An object of class `gazepoint_fold_diagnostics`.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
```

```
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
diagnostics <- diagnose_gazepoint_group_folds(folds)
diagnostics
```

`evaluate_external_validation` *Evaluate an independent external-validation dataset*

Description

Evaluate an independent external-validation dataset

Usage

```
evaluate_external_validation(
  model,
  external_data,
  label = "external",
  threshold = model$threshold,
  bootstrap = 200L,
  seed = 1L
)
```

Arguments

`model`	A fitted `gp3ml_model` object.
`external_data`	Independent external-validation data.
`label`	Label identifying the validation dataset.
`threshold`	Classification probability threshold.
`bootstrap`	Number of calibration bootstrap replicates.
`seed`	Deterministic random seed.

Value

A `gp3ml_external_validation` object containing external predictions, performance metrics, calibration results where applicable, predictor-shift diagnostics, a dataset fingerprint, and task metadata.

Examples

```
training_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
training_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = training_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
model <- train_gazepoint_classifier(
  data = training_data,
  task = task,
  predictors = c("fixation_duration", "pupil_change"),
  engine = "glm",
  seed = 101L
)
external_data <- training_data
external_data$participant_id <- rep(
  sprintf("E%02d", 1:12),
  each = 2
)
external_data$trial_id <- sprintf("ET%02d", 1:24)
external_data$fixation_duration <-
  external_data$fixation_duration + 4
external_data$pupil_change <- cos(seq_len(24) / 4)
validation <- evaluate_external_validation(
  model = model,
  external_data = external_data,
  label = "synthetic_external",
  bootstrap = 10L,
  seed = 101L
)
```

validation

---

evaluate_gazepoint_external_transportability
Evaluate external transportability and validation status

Description

An internal holdout or a dataset explicitly declared non-independent is labelled not_externally_validated; it cannot generate an external- validation claim.

Usage

```
evaluate_gazepoint_external_transportability(
  model,
  development_data,
  external_data = NULL,
  declaration = NULL,
  development_evaluation = NULL,
  threshold = model$threshold,
  bootstrap = 200L,
  seed = 1L
)

## S3 method for class 'gp3ml_transportability_report'
print(x, ...)
```

Arguments

model	Fitted governed model.
development_data	Data used to characterize development schema and group coverage.
external_data	Candidate external data. May be NULL to create an explicit not-validated status.
declaration	External dataset declaration. Required when external data are supplied.
development_evaluation	Optional grouped development evaluation.
threshold	Classification threshold.
bootstrap	Calibration bootstrap replicates.
seed	Deterministic seed.
x	An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.
...	Additional arguments passed to the print method.

Value

A gp3ml_transportability_report object.

evaluate_gazepoint_feature_stability

Evaluate leave-one-feature-out stability

Description

Evaluate leave-one-feature-out stability

Usage

```
evaluate_gazepoint_feature_stability(features, evaluator, ...)
```

Arguments

features	Predictor names.
evaluator	Function called as evaluator(excluded_feature = feature, ...).
...	Additional evaluator arguments.

Value

A gp3ml_stability_evaluation.

evaluate_gazepoint_group_folds

Evaluate a governed model specification across materialized grouped folds

Description

Fits preprocessing and the requested model only on each fold's analysis partition, predicts only on the corresponding assessment partition, retains excluded rows, and records fold-level metrics, leakage audits, warnings, and failures. Row-level predictions are never relabelled as participant- or stimulus-level estimates.

Usage

```
evaluate_gazepoint_group_folds(
  folds,
  task,
  predictors = NULL,
  engine = NULL,
  preprocessor_args = list(),
  engine_args = list(),
  threshold = 0.5,
  seed = 1L,
```

```
  assess_calibration = FALSE,
  calibration_bins = 10L,
  calibration_bootstrap = 0L,
  keep_models = FALSE,
  continue_on_error = TRUE
)

## S3 method for class 'gp3ml_resample_evaluation'
print(x, ...)
```

Arguments

folds	A mature gazepoint_group_folds object containing materialized folds under folds$folds.
task	A governed gp3ml_task compatible with the fold metadata.
predictors	Optional predictor names. Defaults to the fold metadata.
engine	Model engine name or governed custom engine.
preprocessor_args	Arguments passed to fit_gazepoint_preprocessor().
engine_args	Arguments passed to fit_gazepoint_model().
threshold	Classification threshold.
seed	Base deterministic seed.
assess_calibration	Whether to calculate assessment-fold calibration summaries for classification tasks.
calibration_bins	Number of reliability bins.
calibration_bootstrap	Calibration bootstrap replicates. Use zero in fast smoke tests.
keep_models	Whether fitted fold models are retained.
continue_on_error	Whether later folds continue after a failed fold.
x	An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.
...	Additional arguments passed to the print method.

Value

A gp3ml_resample_evaluation object.

Examples

```
data <- simulate_gazepoint_governed_data(12L, 4L, 1L, 101L)
predictors <- c("tracking_ratio", "blink_rate", "gaze_dispersion")
manifest <- create_gazepoint_synthetic_manifest("quality_status", predictors)
folds <- create_gazepoint_group_folds(
```

```
  data = data,
  outcome = "quality_status",
  predictors = predictors,
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
task <- create_gazepoint_synthetic_task(
  data,
  "recording_quality",
  "new_participants"
)
evaluation <- evaluate_gazepoint_group_folds(
  folds,
  task,
  predictors = predictors,
  engine = "glm",
  seed = 101L
)
evaluation
```

`evaluate_gazepoint_missingness_sensitivity` *Evaluate named missingness-sensitivity scenarios*

Description

Evaluate named missingness-sensitivity scenarios

Usage

```
evaluate_gazepoint_missingness_sensitivity(scenarios, evaluator, ...)
```

Arguments

`scenarios`	Named list of scenario objects.
`evaluator`	Function called as `evaluator(scenario = scenario, name = name, ...)`.
`...`	Additional evaluator arguments.

Value

A `gp3ml_stability_evaluation`.

`evaluate_gazepoint_nested_resampling` *Evaluate nested grouped resampling with inner governed tuning*

Description

Evaluate nested grouped resampling with inner governed tuning

Usage

```
evaluate_gazepoint_nested_resampling(
  nested_folds,
  task,
  tuning_grid,
  selection_metric,
  direction,
  predictors = NULL,
  minimum_success_prop = 0.8,
  tie_breakers = NULL,
  selection_rationale = .gp3ml_nested_selection_rationale_default,
  seed = 1L,
  keep_models = FALSE,
  continue_on_error = TRUE
)

## S3 method for class 'gp3ml_nested_evaluation'
print(x, ...)
```

Arguments

`nested_folds`	A `gp3ml_nested_folds` object.
`task`	Governed task.
`tuning_grid`	Explicit tuning grid.
`selection_metric`	Explicit inner selection metric.
`direction`	Explicit selection direction.
`predictors`	Optional predictors.
`minimum_success_prop`	Minimum inner-fold success proportion.
`tie_breakers`	Optional secondary metrics.
`selection_rationale`	Human rationale recorded for each outer fold.
`seed`	Base deterministic seed.
`keep_models`	Whether outer fitted models are retained.

continue_on_error
: Whether failed outer folds remain in the result.

x
: An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.

...
: Additional arguments passed to the print method.

Value

A gp3ml_nested_evaluation object retaining inner tuning results, selections, outer predictions, metrics, and failures.

---

evaluate_gazepoint_seed_stability
Evaluate seed stability

Description

Evaluate seed stability

Usage

```
evaluate_gazepoint_seed_stability(seeds, evaluator, ...)
```

Arguments

seeds
: Integer seeds.

evaluator
: Function called as evaluator(seed = seed, ...).

...
: Additional evaluator arguments.

Value

A gp3ml_stability_evaluation.

---

evaluate_gazepoint_thresholds
Evaluate explicit classification thresholds

Description

Evaluate explicit classification thresholds

Usage

```
evaluate_gazepoint_thresholds(
  truth,
  probability,
  positive,
  thresholds,
  cost_false_positive = 1,
  cost_false_negative = 1
)
```

Arguments

truth	Observed binary outcome.
probability	Probability of the positive class.
positive	Positive class label.
thresholds	Explicit candidate thresholds.
cost_false_positive	False-positive cost.
cost_false_negative	False-negative cost.

Value

A gp3ml_threshold_evaluation.

---

evaluate_gazepoint_threshold_stability

Evaluate threshold stability around the optimum

Description

Evaluate threshold stability around the optimum

Usage

```
evaluate_gazepoint_threshold_stability(
  evaluation,
  metric,
  direction = c("maximize", "minimize"),
  tolerance = 0.02
)
```

Arguments

evaluation	Threshold evaluation.
metric	Metric.
direction	Optimization direction.
tolerance	Fractional tolerance from the optimum.

Value

A gp3ml_threshold_stability.

---

fit_gazepoint_calibrator

Fit a probability calibrator

Description

Fit a probability calibrator

Usage

```
fit_gazepoint_calibrator(
  truth,
  probability,
  positive = NULL,
  method = c("platt", "isotonic")
)
```

Arguments

truth	Observed binary outcome values.
probability	Uncalibrated positive-class probabilities.
positive	Label representing the positive class.
method	Calibration method: Platt scaling or isotonic regression.

Value

A fitted gp3ml_calibrator object containing the calibration method, fitted model, and outcome labels.

Examples

```
truth <- factor(
  rep(c("pass", "review"), 6),
  levels = c("pass", "review")
)
probability <- c(
  0.20, 0.70, 0.60, 0.55, 0.30, 0.80,
  0.65, 0.45, 0.40, 0.75, 0.50, 0.60
)
calibrator <- fit_gazepoint_calibrator(
  truth = truth,
  probability = probability,
  positive = "review",
  method = "platt"
)
calibrator
```

---

fit_gazepoint_conformal

Fit target-aware split-conformal calibration

Description

This function provides conservative split-conformal calibration for explicitly observed regression or binary classification outcomes. When a grouped calibration unit is supplied, row scores are aggregated to the maximum score within each calibration unit before the conformal quantile is estimated. This records and respects the calibration unit but does not claim distribution-free coverage under arbitrary dependence.

Usage

```
fit_gazepoint_conformal(
  truth,
  prediction = NULL,
  probability = NULL,
  task_type = c("regression", "classification"),
  positive = NULL,
  level = 0.9,
 calibration_unit = c("observation", "participant", "stimulus", "participant_stimulus"),
  unit = NULL,
  generalization_target
)
```

Arguments

truth	Observed calibration outcomes.
prediction	Numeric predictions for regression.

probability	Positive-class probabilities for classification.
task_type	"regression" or "classification".
positive	Positive class label for classification.
level	Nominal coverage level.
calibration_unit	Calibration unit.
unit	Optional group identifier for grouped calibration.
generalization_target	Declared generalization target.

Value

A gp3ml_conformal_fit.

---

fit_gazepoint_deep_model *Fit an optional governed deep-learning model through keras3*

Description

Fit an optional governed deep-learning model through keras3

Usage

```
fit_gazepoint_deep_model(
  data,
  task,
  predictors = NULL,
  preprocessor = NULL,
  hidden_units = c(64L, 32L),
  dropout = 0.2,
  epochs = 50L,
  batch_size = 32L,
  validation_split = 0.2,
  optimizer = "adam",
  seed = 1L,
  verbose = 0L
)
```

Arguments

data	Analysis data used to fit the network.
task	A governed gp3ml_task object.
predictors	Optional character vector of predictor columns.
preprocessor	Optional fitted preprocessing object.

hidden_units	Integer vector of hidden-layer sizes.
dropout	Dropout proportion applied after hidden layers.
epochs	Number of training epochs.
batch_size	Training batch size.
validation_split	Proportion reserved for internal validation.
optimizer	Keras optimizer name or object.
seed	Deterministic random seed.
verbose	Keras training verbosity.

Value

A governed gp3ml_model object containing the fitted keras3 model, training history, preprocessing object, task contract, and training metadata.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = example_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
deep_model <- fit_gazepoint_deep_model(
  data = example_data,
  task = task,
  predictors = c("fixation_duration", "pupil_change"),
```

```
  hidden_units = 4L,
  dropout = 0,
  epochs = 1L,
  batch_size = 8L,
  validation_split = 0,
  seed = 101L,
  verbose = 0L
)
deep_model
```

`fit_gazepoint_model` *Fit a governed Gazepoint model*

Description

Fit a governed Gazepoint model

Usage

```
fit_gazepoint_model(
  data,
  task,
  predictors = NULL,
  engine = NULL,
  preprocessor = NULL,
  preprocessor_args = list(),
  engine_args = list(),
  seed = 1L,
  threshold = 0.5
)
```

Arguments

`data`	Analysis data used to fit the model.
`task`	A governed `gp3ml_task` object.
`predictors`	Optional character vector of predictor columns.
`engine`	Engine name or controlled custom-engine object.
`preprocessor`	Optional fitted preprocessing object.
`preprocessor_args`	Arguments passed to preprocessing fitting.
`engine_args`	Arguments passed to the model engine.
`seed`	Deterministic random seed.
`threshold`	Classification probability threshold.

Value

A governed gp3ml_model object containing the fitted engine, preprocessing object, task contract, predictors, and training metadata.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = example_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
model <- fit_gazepoint_model(
  data = example_data,
  task = task,
  predictors = c("fixation_duration", "pupil_change"),
  engine = "glm",
  seed = 101L
)
model
```

---

fit_gazepoint_preprocessor

Fit a fold-local preprocessing engine

Description

Fit a fold-local preprocessing engine

Usage

```
fit_gazepoint_preprocessor(
  data,
  predictors,
  numeric_imputation = c("median", "mean"),
  center = TRUE,
  scale = TRUE,
  novel_level = c("other", "error"),
  remove_zero_variance = TRUE
)
```

Arguments

`data`	Analysis data used to estimate preprocessing parameters.
`predictors`	Character vector naming predictor columns.
`numeric_imputation`	Numeric imputation method.
`center`	Whether numeric model columns should be centered.
`scale`	Whether numeric model columns should be scaled.
`novel_level`	How novel categorical levels should be handled.
`remove_zero_variance`	Whether zero-variance columns are removed.

Value

A fitted `gp3ml_preprocessor` object containing analysis-partition imputation values, factor levels, model columns, centering values, and scaling values.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
```

```
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
preprocessor <- fit_gazepoint_preprocessor(
  data = example_data,
  predictors = c(
    "fixation_duration",
    "pupil_change",
    "condition"
  )
)
preprocessor
```

`gazepoint_classification_metrics` *Binary classification metrics*

Description

Binary classification metrics

Usage

```
gazepoint_classification_metrics(
  truth,
  probability,
  predicted = NULL,
  positive = NULL,
  threshold = 0.5
)
```

Arguments

`truth`	Observed binary outcome values.
`probability`	Predicted positive-class probabilities.
`predicted`	Optional predicted classes.
`positive`	Label representing the positive class.
`threshold`	Probability threshold used for class predictions.

Value

A one-row data frame containing the sample size, threshold, class-performance measures, discrimination metrics, Brier score, and log loss.

Examples

```
truth <- factor(
  rep(c("pass", "review"), 6),
  levels = c("pass", "review")
)
probability <- c(
  0.20, 0.70, 0.60, 0.55, 0.30, 0.80,
  0.65, 0.45, 0.40, 0.75, 0.50, 0.60
)
predicted <- factor(
  ifelse(probability >= 0.5, "review", "pass"),
  levels = levels(truth)
)
gazepoint_classification_metrics(
  truth = truth,
  probability = probability,
  predicted = predicted,
  positive = "review"
)
```

---

gazepoint_performance_metrics

Task-aware performance metrics

Description

Task-aware performance metrics

Usage

```
gazepoint_performance_metrics(
  task,
  truth,
  prediction = NULL,
  probability = NULL,
  threshold = 0.5
)
```

Arguments

task	A governed gp3ml_task object.
truth	Observed outcome values.
prediction	Predicted classes or numeric values.
probability	Predicted positive-class probabilities.
threshold	Probability threshold for classification.

Value

A one-row data frame of classification or regression metrics selected according to the governed task type.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = example_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
probability <- seq(
  0.20,
  0.80,
  length.out = nrow(example_data)
)
predicted <- factor(
  ifelse(probability >= 0.5, "review", "pass"),
  levels = levels(example_data$quality_status)
)
gazepoint_performance_metrics(
  task = task,
  truth = example_data$quality_status,
  prediction = predicted,
  probability = probability
)
```

gazepoint_regression_metrics *Regression metrics*

Description

Regression metrics

Usage

```
gazepoint_regression_metrics(truth, prediction)
```

Arguments

truth	Observed numeric outcome values.
prediction	Predicted numeric outcome values.

Value

A one-row data frame containing the sample size, RMSE, MAE, R-squared value, and prediction correlation.

Examples

```
truth <- c(1.0, 2.0, 3.0, 4.0, 5.0)
prediction <- c(1.1, 1.8, 3.2, 3.9, 4.8)
gazepoint_regression_metrics(truth, prediction)
```

gp3ml_api_contracts *gp3ml public API contracts*

Description

Returns the package's explicit compatibility contract for the public API. APIs classified as stable in version 0.2.0 remain stable throughout the 0.3.x line. New APIs introduced by the current development milestone are marked experimental until promoted by a later release decision.

Usage

```
gp3ml_api_contracts()
```

Value

A gp3ml_api_contract_registry object.

gp3ml_available_engines *List available model engines*

Description

List available model engines

Usage

```
gp3ml_available_engines()
```

Value

A data frame listing supported model-engine names and whether each optional engine is currently available.

Examples

```
gp3ml_available_engines()
```

gp3ml_engine_capabilities *Audit gp3ml model-engine capabilities*

Description

Audit gp3ml model-engine capabilities

Usage

```
gp3ml_engine_capabilities(check_keras_backend = FALSE)
```

Arguments

check_keras_backend	Whether to query the configured Keras backend.

Value

A gp3ml_engine_capabilities data frame.

gp3ml_interop_contracts *Cross-package interoperability contracts*

Description

Describes a lightweight handoff boundary. Upstream packages remain responsible for their own importing, cleaning, feature derivation, signal processing, sequence processing, and quality control. gp3ml receives already prepared observed variables together with explicit provenance.

Usage

```
gp3ml_interop_contracts()
```

Value

A data frame describing supported handoff sources and responsibilities.

gp3ml_object_schema *Describe the schema of a gp3ml object*

Description

Describe the schema of a gp3ml object

Usage

```
gp3ml_object_schema(x, recursive = FALSE)
```

Arguments

x	Object to inspect.
recursive	Whether to include one level of nested named-list components.

Value

A data frame describing component names, classes, storage types, lengths, and dimensions.

gp3ml_prohibited_uses *Prohibited gp3ml uses*

Description

Prohibited gp3ml uses

Usage

```
gp3ml_prohibited_uses()
```

Value

A character vector of prohibited use descriptions.

Examples

```
gp3ml_prohibited_uses()
```

integrate_black_box_model *Integrate a controlled black-box model engine*

Description

Integrate a controlled black-box model engine

Usage

```
integrate_black_box_model(
  name,
  fit_fun,
  predict_fun,
  supports = c("classification", "regression"),
  probability = TRUE,
  metadata = list(),
  safety_declaration
)
```

Arguments

name	Unique name for the custom engine.
fit_fun	Function that fits the custom engine.
predict_fun	Function that generates predictions.
supports	Task types supported by the engine.
probability	Whether classification probabilities are supported.
metadata	Optional engine metadata.
safety_declaration	Named logical safety declarations.

Value

A controlled gp3ml_engine object containing the custom fit and prediction functions, supported task types, metadata, and explicit safety declarations.

Examples

```
custom_fit <- function(x, y, task, args) {
  training_data <- data.frame(
    .outcome = y,
    x,
    check.names = FALSE
  )
  stats::glm(
    .outcome ~ .,
    data = training_data,
    family = stats::binomial()
  )
}
custom_predict <- function(fit, newdata, type, task, ...) {
  as.numeric(stats::predict(
    fit,
    newdata = as.data.frame(newdata),
    type = "response"
  ))
}
engine <- integrate_black_box_model(
  name = "custom_glm",
  fit_fun = custom_fit,
  predict_fun = custom_predict,
  supports = "classification",
  probability = TRUE,
  safety_declaration = list(
    prohibited_uses_acknowledged = TRUE,
    prediction_time_inputs_only = TRUE,
    group_aware_evaluation_required = TRUE
  )
)
engine$name
```

```
engine$supports
engine$probability
engine$safety_declaration
```

`lock_gazepoint_analysis_plan` *Lock an analysis plan using SHA-256*

Description

Lock an analysis plan using SHA-256

Usage

```
lock_gazepoint_analysis_plan(plan, plan_id = NULL, locked_at = Sys.time())
```

Arguments

`plan`	A valid unlocked plan.
`plan_id`	Optional stable identifier.
`locked_at`	Optional lock time.

Value

A locked `gp3ml_analysis_plan`.

`normalize_gazepoint_artifact_text` *Normalize volatile text in generated research artifacts*

Description

Normalize volatile text in generated research artifacts

Usage

```
normalize_gazepoint_artifact_text(x, project_path = NULL)
```

Arguments

`x`	Character vector.
`project_path`	Optional project path to replace by `<PROJECT>`.

Value

Character vector with volatile runtime fragments normalized.

plot.gp3ml_abstention_audit *Plot abstention audit*

Description

Plot abstention audit

Usage

```
## S3 method for class 'gp3ml_abstention_audit'
plot(x, ...)
```

Arguments

x	A gp3ml_abstention_audit.
...	Additional arguments passed to graphics::barplot().

plot.gp3ml_api_stability_audit *Plot a gp3ml API stability audit*

Description

Plot a gp3ml API stability audit

Usage

```
## S3 method for class 'gp3ml_api_stability_audit'
plot(x, ...)
```

Arguments

x	A gp3ml_api_stability_audit.
...	Additional graphical parameters.

plot.gp3ml_conformal_coverage *Plot conformal coverage*

Description

Plot conformal coverage

Usage

```
## S3 method for class 'gp3ml_conformal_coverage'
plot(x, ...)
```

Arguments

x	A gp3ml_conformal_coverage.
...	Additional arguments passed to graphics::barplot().

plot.gp3ml_dataset_shift_audit *Plot a dataset shift audit*

Description

Plot a dataset shift audit

Usage

```
## S3 method for class 'gp3ml_dataset_shift_audit'
plot(x, ...)
```

Arguments

x	A gp3ml_dataset_shift_audit.
...	Additional arguments passed to graphics::barplot().

plot.gp3ml_engine_capabilities *Plot gp3ml engine availability*

Description

Plot gp3ml engine availability

Usage

```
## S3 method for class 'gp3ml_engine_capabilities'
plot(x, ...)
```

Arguments

x	Engine-capability table.
...	Additional graphical parameters.

plot.gp3ml_environment_comparison *Plot an environment comparison*

Description

Plot an environment comparison

Usage

```
## S3 method for class 'gp3ml_environment_comparison'
plot(x, ...)
```

Arguments

x	An environment comparison.
...	Additional arguments passed to `graphics::barplot()`.

plot.gp3ml_governance_profile_audit

Plot a governance profile audit

Description

Plot a governance profile audit

Usage

```
## S3 method for class 'gp3ml_governance_profile_audit'
plot(x, ...)
```

Arguments

x	Governance profile audit.
...	Additional arguments passed to graphics::barplot().

plot.gp3ml_handoff_validation

Plot handoff validation checks

Description

Plot handoff validation checks

Usage

```
## S3 method for class 'gp3ml_handoff_validation'
plot(x, ...)
```

Arguments

x	A gp3ml_handoff_validation.
...	Additional graphical parameters.

plot.gp3ml_model_artifact_validation
Plot model-artifact validation

Description

Plot model-artifact validation

Usage

```
## S3 method for class 'gp3ml_model_artifact_validation'
plot(x, ...)
```

Arguments

x	A gp3ml_model_artifact_validation.
...	Additional arguments passed to graphics::barplot().

plot.gp3ml_model_robustness_audit
Plot a robustness audit

Description

Plot a robustness audit

Usage

```
## S3 method for class 'gp3ml_model_robustness_audit'
plot(x, ...)
```

Arguments

x	A gp3ml_model_robustness_audit.
...	Additional arguments passed to graphics::barplot().

`plot.gp3ml_plan_deviation_audit`
Plot analysis-plan deviations

Description

Plot analysis-plan deviations

Usage

```
## S3 method for class 'gp3ml_plan_deviation_audit'
plot(x, ...)
```

Arguments

`x`	A `gp3ml_plan_deviation_audit`.
`...`	Additional arguments passed to `graphics::barplot()`.

`plot.gp3ml_release_checksum_validation`
Plot release checksum validation

Description

Plot release checksum validation

Usage

```
## S3 method for class 'gp3ml_release_checksum_validation'
plot(x, ...)
```

Arguments

`x`	Release checksum validation.
`...`	Additional arguments passed to `graphics::barplot()`.

plot.gp3ml_reproducibility_audit *Plot a reproducibility-hardening audit*

Description

Plot a reproducibility-hardening audit

Usage

```
## S3 method for class 'gp3ml_reproducibility_audit'
plot(x, ...)
```

Arguments

x	A gp3ml_reproducibility_audit.
...	Additional graphical parameters.

plot.gp3ml_research_bundle_validation *Plot research-bundle validation*

Description

Plot research-bundle validation

Usage

```
## S3 method for class 'gp3ml_research_bundle_validation'
plot(x, ...)
```

Arguments

x	A gp3ml_research_bundle_validation.
...	Additional graphical parameters.

plot.gp3ml_ro_crate_validation *Plot RO-Crate validation*

Description

Plot RO-Crate validation

Usage

```
## S3 method for class 'gp3ml_ro_crate_validation'
plot(x, ...)
```

Arguments

x	A gp3ml_ro_crate_validation.
...	Additional arguments passed to graphics::barplot().

plot.gp3ml_threshold_evaluation *Plot threshold evaluation*

Description

Plot threshold evaluation

Usage

```
## S3 method for class 'gp3ml_threshold_evaluation'
plot(x, metric = "balanced_accuracy", ...)
```

Arguments

x	A gp3ml_threshold_evaluation.
metric	Metric to plot.
...	Additional arguments passed to graphics::plot().

`predict.gp3ml_model` *Predict from a gp3ml model*

Description

Predict from a gp3ml model

Usage

```
## S3 method for class 'gp3ml_model'
predict(
  object,
  newdata,
  type = c("response", "probability", "class", "link"),
  ...
)
```

Arguments

`object`	A fitted `gp3ml_model` object.
`newdata`	New data containing the required predictors.
`type`	Requested prediction type.
`...`	Additional arguments passed to custom prediction methods.

Value

For classification with `type = "class"`, a factor of predicted classes. Otherwise, a numeric vector of probabilities, link-scale values, or regression predictions.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
```

```
)
task <- declare_gazepoint_task(
  data = example_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
model <- train_gazepoint_classifier(
  data = example_data,
  task = task,
  predictors = c("fixation_duration", "pupil_change"),
  engine = "glm",
  seed = 101L
)
probability <- predict(
  model,
  example_data,
  type = "probability"
)
predicted_class <- predict(
  model,
  example_data,
  type = "class"
)
head(probability)
head(predicted_class)
```

`predict_gazepoint_interval` *Predict conformal regression intervals*

Description

Predict conformal regression intervals

Usage

```
predict_gazepoint_interval(object, prediction)
```

Arguments

`object`	A regression `gp3ml_conformal_fit`.
`prediction`	Point predictions.

Value

Data frame with point prediction, lower, and upper limits.

---

predict_gazepoint_set *Predict binary conformal prediction sets*

Description

Predict binary conformal prediction sets

Usage

```
predict_gazepoint_set(object, probability)
```

Arguments

object	A classification gp3ml_conformal_fit.
probability	Positive-class probabilities.

Value

A data frame containing set membership and a readable set label.

---

print.gazepoint_feature_manifest_validation *Print feature-manifest validation*

Description

Print feature-manifest validation

Usage

```
## S3 method for class 'gazepoint_feature_manifest_validation'
print(x, ...)
```

Arguments

x	An object returned by validate_gazepoint_feature_manifest().
...	Additional arguments, currently unused.

Value

x, invisibly.

Examples

```
manifest <- create_gazepoint_feature_manifest(
  features = "fixation_duration",
  scientific_source = "Gazepoint fixation export",
  source_table = "fixations",
  transformation = "Trial-level mean",
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
validation <- validate_gazepoint_feature_manifest(manifest)
print(validation)
```

---

print.gazepoint_fold_diagnostics

Print Gazepoint fold diagnostics

Description

Print Gazepoint fold diagnostics

Usage

```
## S3 method for class 'gazepoint_fold_diagnostics'
print(x, ...)
```

Arguments

x	A gazepoint_fold_diagnostics object.
...	Additional arguments, currently unused.

Value

x, invisibly.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
```

```
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
diagnostics <- diagnose_gazepoint_group_folds(folds)
print(diagnostics)
```

print.gazepoint_fold_diagnostics_validation
Print Gazepoint fold-diagnostics validation

Description

Print Gazepoint fold-diagnostics validation

Usage

```
## S3 method for class 'gazepoint_fold_diagnostics_validation'
print(x, ...)
```

Arguments

x	A gazepoint_fold_diagnostics_validation object.
...	Additional arguments, currently unused.

Value

x, invisibly.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
```

```
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
diagnostics <- diagnose_gazepoint_group_folds(folds)
validation <- validate_gazepoint_fold_diagnostics(
  diagnostics
)
print(validation)
```

`print.gazepoint_group_folds` *Print group-aware Gazepoint resampling folds*

Description

Print group-aware Gazepoint resampling folds

Usage

```
## S3 method for class 'gazepoint_group_folds'
print(x, ...)
```

Arguments

x	A gazepoint_group_folds object.
...	Additional arguments, currently unused.

Value

x, invisibly.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
```

```
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
print(folds)
```

`print.gazepoint_group_folds_audit` *Print aggregated group-fold leakage auditing*

Description

Print aggregated group-fold leakage auditing

Usage

```
## S3 method for class 'gazepoint_group_folds_audit'
print(x, ...)
```

Arguments

`x`	A `gazepoint_group_folds_audit` object.
`...`	Additional arguments, currently unused.

Value

`x`, invisibly.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
```

```
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
audit <- audit_gazepoint_group_folds(folds)
print(audit)
```

`print.gazepoint_group_folds_validation` *Print group-aware fold validation*

Description

Print group-aware fold validation

Usage

```
## S3 method for class 'gazepoint_group_folds_validation'
print(x, ...)
```

Arguments

`x`	A `gazepoint_group_folds_validation` object.
`...`	Additional arguments, currently unused.

Value

`x`, invisibly.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
```

```
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
validation <- validate_gazepoint_group_folds(folds)
print(validation)
```

print.gazepoint_ml_leakage_audit *Print a Gazepoint ML leakage audit*

Description

Print a Gazepoint ML leakage audit

Usage

```
## S3 method for class 'gazepoint_ml_leakage_audit'
print(x, ...)
```

Arguments

x	An object returned by audit_gazepoint_ml_leakage().
...	Additional arguments, currently unused.

Value

x, invisibly.

Examples

```
analysis <- data.frame(
  participant_id = c("P01", "P01", "P02", "P02"),
  trial_id = c("T01", "T02", "T03", "T04"),
  stimulus_id = c("S01", "S02", "S03", "S04"),
  outcome = c(0, 1, 0, 1),
  fixation_duration = c(210, 240, 225, 260),
  pupil_change = c(0.10, 0.16, 0.12, 0.18)
)
assessment <- data.frame(
  participant_id = c("P03", "P03", "P04", "P04"),
  trial_id = c("T05", "T06", "T07", "T08"),
  stimulus_id = c("S05", "S06", "S07", "S08"),
  outcome = c(1, 0, 1, 0),
  fixation_duration = c(275, 230, 290, 245),
  pupil_change = c(0.21, 0.11, 0.24, 0.14)
)
audit <- audit_gazepoint_ml_leakage(
  analysis = analysis,
  assessment = assessment,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants"
```

```
)
print(audit)
```

`print.gazepoint_ml_split` *Print a group-aware Gazepoint split*

Description

Print a group-aware Gazepoint split

Usage

```
## S3 method for class 'gazepoint_ml_split'
print(x, ...)
```

Arguments

`x`	A `gazepoint_ml_split` object.
`...`	Additional arguments, currently unused.

Value

`x`, invisibly.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
```

```
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
split <- split_gazepoint_ml_data(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  assessment_prop = 1 / 3,
  seed = 101L
)
print(split)
```

`print.gazepoint_ml_split_validation` *Print group-aware split validation*

Description

Print group-aware split validation

Usage

```
## S3 method for class 'gazepoint_ml_split_validation'
print(x, ...)
```

Arguments

x	An object returned by validate_gazepoint_ml_split().
...	Additional arguments, currently unused.

Value

x, invisibly.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
```

```
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
split <- split_gazepoint_ml_data(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  assessment_prop = 1 / 3,
  seed = 101L
)
validation <- validate_gazepoint_ml_split(split)
print(validation)
```

`restore_gazepoint_model_artifact` *Restore a model artifact*

Description

Restore a model artifact

Usage

```
restore_gazepoint_model_artifact(artifact)
```

Arguments

`artifact`	A model artifact.

Value

A restored artifact with an unbundled model where needed.

`select_gazepoint_model` *Select a governed candidate using an explicit metric and direction*

Description

This function records a reviewable decision. It does not refit a model and refuses accuracy as the sole primary metric.

Usage

```
select_gazepoint_model(
  x,
  metric,
  direction,
  minimum_success_prop = 0.8,
  tie_breakers = NULL,
  rationale
)

## S3 method for class 'gp3ml_model_selection'
print(x, ...)
```

Arguments

`x`	A `gp3ml_model_tuning` object.
`metric`	Explicit primary metric.
`direction`	Explicit optimization direction.
`minimum_success_prop`	Minimum successful-fold proportion.
`tie_breakers`	Optional ordered secondary metric names.
`rationale`	Required human-readable selection rationale.
`...`	Additional arguments passed to the print method.

Value

A `gp3ml_model_selection` object.

`select_gazepoint_threshold` *Select a threshold from a governed threshold evaluation*

Description

Select a threshold from a governed threshold evaluation

Usage

```
select_gazepoint_threshold(
  evaluation,
  metric,
  direction = c("maximize", "minimize"),
  threshold_origin = c("inner_resampling", "training"),
  training_partition = "inner_resampling",
  generalization_target,
  scientific_justification,
  abstention_allowed = FALSE,
  abstention_interval = NULL
)
```

Arguments

`evaluation`	A `gp3ml_threshold_evaluation`.
`metric`	Metric column to optimize.
`direction`	`"maximize"` or `"minimize"`.
`threshold_origin`	Must identify an analysis/training source.
`training_partition`	Partition used to select the threshold.
`generalization_target`	Declared target.
`scientific_justification`	Explicit justification.
`abstention_allowed`	Whether abstention is allowed.
`abstention_interval`	Optional abstention interval.

Value

A `gp3ml_decision_rule`.

`simulate_gazepoint_governed_data` *Simulate governed synthetic Gazepoint-derived data*

Description

Creates deterministic, non-sensitive synthetic data for package examples, tests, and website articles. The generated outcomes are explicitly observed: a predefined recording-quality review status, an experimentally assigned condition, and a non-sensitive recorded response.

Usage

```
simulate_gazepoint_governed_data(
  n_participants = 30L,
  n_stimuli = 8L,
  trials_per_cell = 2L,
  seed = 1L
)
```

Arguments

`n_participants`	Number of synthetic participants.
`n_stimuli`	Number of synthetic stimuli.
`trials_per_cell`	Number of trials per participant-stimulus cell.
`seed`	Deterministic random seed.

Value

A data frame containing identifiers, observed outcomes, and predeclared synthetic predictors.

Examples

```
synthetic <- simulate_gazepoint_governed_data(
  n_participants = 12L,
  n_stimuli = 4L,
  trials_per_cell = 1L,
  seed = 101L
)
table(synthetic$quality_status)
```

simulate_gazepoint_research_handoffs

Simulate realistic cross-package Gazepoint research handoffs

Description

Generates deterministic, shareable, synthetic prepared outputs representing handoffs from gp3tools, gpbiometrics, and gp3sequences. The outcome is an experimentally assigned condition. Biometrics variables are signal-quality summaries only; no health, emotion, stress, cognition, or other mental-state outcome is generated or inferred.

Usage

```
simulate_gazepoint_research_handoffs(
  n_participants = 24L,
  n_stimuli = 6L,
  trials_per_stimulus = 1L,
  seed = 3001L
)
```

Arguments

n_participants	Number of participants.
n_stimuli	Number of stimuli.
trials_per_stimulus	Trials per participant-stimulus cell.
seed	Deterministic seed.

Value

A gp3ml_research_bundle.

split_gazepoint_ml_data

Create a deterministic group-aware Gazepoint holdout split

Description

Creates analysis and assessment partitions that preserve the grouping unit implied by an explicit generalization target.

Usage

```
split_gazepoint_ml_data(
  data,
  outcome,
  predictors,
  feature_manifest,
  generalization_target,
  participant_id = NULL,
  trial_id = NULL,
  stimulus_id = NULL,
  assessment_prop = 0.2,
  seed = 1L,
  source_row_id = ".gp3ml_source_row"
)
```

Arguments

`data`	Data frame containing the outcome, predictors, and grouping identifiers.
`outcome`	Name of the outcome column.
`predictors`	Character vector of predictor-column names.
`feature_manifest`	Feature manifest containing the predictors.
`generalization_target`	Declared predictive-generalization target.
`participant_id`	Optional participant-identifier column.
`trial_id`	Optional trial-identifier column.
`stimulus_id`	Optional stimulus-identifier column.
`assessment_prop`	Requested assessment proportion.
`seed`	Integer random seed.
`source_row_id`	Name of the source-row identifier added to the returned partitions.

Details

For simultaneous participant and stimulus generalization, cross-block rows are placed in the excluded partition.

This function does not perform preprocessing, feature selection, resampling, or model fitting.

Value

An object of class `gazepoint_ml_split`.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
split <- split_gazepoint_ml_data(
  data = example_data,
```

```
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  assessment_prop = 1 / 3,
  seed = 101L
)
split
```

`summarize_gazepoint_resample_performance` *Summarize repeated grouped-resampling performance*

Description

Summarize repeated grouped-resampling performance

Usage

```
summarize_gazepoint_resample_performance(
  x,
  aggregation = c("fold_distribution", "pooled_rows"),
  conf_level = 0.95
)

## S3 method for class 'gp3ml_resample_performance_summary'
print(x, ...)
```

Arguments

`x`	A `gp3ml_resample_evaluation`.
`aggregation`	Either fold-distribution summaries or pooled row-level predictions. Pooled rows are explicitly labelled and do not change the generalization unit.
`conf_level`	Confidence level for fold-distribution quantiles.
`...`	Additional arguments passed to the print method.

Value

A `gp3ml_resample_performance_summary` object.

summarize_gazepoint_resample_uncertainty

Summarize uncertainty across folds or repeats

Description

Summarize uncertainty across folds or repeats

Usage

```
summarize_gazepoint_resample_uncertainty(
  evaluation,
  unit = c("fold", "repeat"),
  conf_level = 0.95
)

## S3 method for class 'gp3ml_resample_uncertainty'
print(x, ...)
```

Arguments

evaluation	A gp3ml_resample_evaluation or gp3ml_nested_evaluation.
unit	Distribution unit: individual folds or repeat means.
conf_level	Quantile interval level.
x	An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.
...	Additional arguments passed to the print method.

Value

A gp3ml_resample_uncertainty object.

summarize_gazepoint_shift

Summarize dataset shift without collapsing it to one drift score

Description

Summarize dataset shift without collapsing it to one drift score

Usage

```
summarize_gazepoint_shift(shift, missingness = NULL)
```

Arguments

shift	A dataset-shift audit.
missingness	Optional missingness-shift audit.

Value

A structured summary.

---

test_gazepoint_model_portability

Test model-artifact serialization and optional fresh-process prediction

---

Description

Test model-artifact serialization and optional fresh-process prediction

Usage

```
test_gazepoint_model_portability(
  artifact,
  newdata = artifact$reference_data,
  tolerance = 1e-08,
  fresh_process = FALSE
)
```

Arguments

artifact	Model artifact.
newdata	Optional prediction fixture.
tolerance	Numeric prediction tolerance.
fresh_process	Whether to test in a fresh R process using `callr`.

Value

A `gp3ml_model_portability_test`.

`train_gazepoint_classifier` *Generic governed binary-classifier training wrapper*

Description

Generic governed binary-classifier training wrapper

Usage

```
train_gazepoint_classifier(data, task, predictors = NULL, engine = "glm", ...)
```

Arguments

`data`	Analysis data used to train the classifier.
`task`	A governed binary-classification task.
`predictors`	Optional character vector of predictor columns.
`engine`	Classification engine name or custom engine.
`...`	Additional arguments passed to `fit_gazepoint_model()`.

Value

A governed classification `gp3ml_model` object returned by `fit_gazepoint_model()`.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = example_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
```

```
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
model <- train_gazepoint_classifier(
  data = example_data,
  task = task,
  predictors = c("fixation_duration", "pupil_change"),
  engine = "glm",
  seed = 101L
)
model
```

`tune_gazepoint_model` *Evaluate every governed candidate on the same grouped folds*

Description

Evaluate every governed candidate on the same grouped folds

Usage

```
tune_gazepoint_model(
  folds,
  task,
  tuning_grid,
  predictors = NULL,
  metrics = NULL,
  seed = 1L,
  continue_on_error = TRUE,
  keep_evaluations = TRUE
)

## S3 method for class 'gp3ml_model_tuning'
print(x, ...)
```

Arguments

`folds`	A `gazepoint_group_folds` object.
`task`	A governed task.
`tuning_grid`	A `gp3ml_tuning_grid`.
`predictors`	Optional declared predictors.
`metrics`	Optional metric names retained in the comparison table.
`seed`	Base deterministic seed.

continue_on_error
: Whether failed candidates remain in the result while later candidates continue.

keep_evaluations
: Whether complete candidate evaluations are retained.

x
: An object returned by the corresponding gp3ml constructor, evaluator, summarizer, or validator.

...
: Additional arguments passed to the print method.

Value

A gp3ml_model_tuning object retaining all candidates and failures.

Examples

```
data <- simulate_gazepoint_governed_data(12L, 4L, 1L, 202L)
predictors <- c("tracking_ratio", "blink_rate", "gaze_dispersion")
manifest <- create_gazepoint_synthetic_manifest("quality_status", predictors)
folds <- create_gazepoint_group_folds(
  data, "quality_status", predictors, manifest,
  "new_participants", "participant_id", "trial_id", "stimulus_id",
  v = 3L, repeats = 1L, seed = 202L
)
task <- create_gazepoint_synthetic_task(data, "recording_quality", "new_participants")
grid <- create_gazepoint_tuning_grid(
  "glm",
  preprocessor_grid = list(center = c(TRUE, FALSE), scale = TRUE),
  thresholds = 0.5
)
tuned <- tune_gazepoint_model(folds, task, grid, predictors, seed = 202L)
tuned
```

---

validate_gazepoint_analysis_plan

Validate an analysis plan

Description

Validate an analysis plan

Usage

```
validate_gazepoint_analysis_plan(plan)
```

Arguments

plan
: A gp3ml_analysis_plan.

Value

A validation object.

validate_gazepoint_conformal *Validate a conformal fit*

Description

Validate a conformal fit

Usage

```
validate_gazepoint_conformal(object)
```

Arguments

object	A conformal fit.

Value

A validation object.

validate_gazepoint_decision_rule *Validate a governed decision rule*

Description

Validate a governed decision rule

Usage

```
validate_gazepoint_decision_rule(rule, require_threshold = FALSE)
```

Arguments

rule	A gp3ml_decision_rule.
require_threshold	Whether a concrete threshold is required.

Value

A validation object.

validate_gazepoint_environment

Validate the current environment against a reference record

Description

Validate the current environment against a reference record

Usage

```
validate_gazepoint_environment(reference, root = ".", include_renv = FALSE)
```

Arguments

reference	Reference environment record.
root	Project root.
include_renv	Whether to compare renv lock hashes.

Value

An environment comparison.

validate_gazepoint_feature_manifest

Validate a Gazepoint feature-provenance manifest

Description

Validates the schema and declared scientific safeguards in a feature manifest. Schema errors stop execution. Substantive concerns are returned as structured `pass`, `review`, or `fail` checks.

Usage

```
validate_gazepoint_feature_manifest(x)
```

Arguments

x	A feature manifest created by `create_gazepoint_feature_manifest()` or a compatible data frame.

Details

A manifest fails when an intended predictor is declared as outcome-derived, post-outcome, unavailable at prediction time, or an identifier. It also fails when fold-local estimation is required but preprocessing is declared outside the resampling fold.

Unknown or incomplete provenance is returned for review rather than treated as evidence that a safeguard was satisfied.

Value

An object of class gazepoint_feature_manifest_validation containing the overall status, complete checks, non-passing issues, and validated manifest.

Examples

```
manifest <- create_gazepoint_feature_manifest(
  features = "fixation_duration",
  scientific_source = "Gazepoint fixation export",
  source_table = "fixations",
  transformation = "Trial-level mean",
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)

validate_gazepoint_feature_manifest(manifest)
```

---

validate_gazepoint_fold_diagnostics

Validate Gazepoint fold diagnostics

Description

Validate Gazepoint fold diagnostics

Usage

```
validate_gazepoint_fold_diagnostics(x)
```

Arguments

x	A gazepoint_fold_diagnostics object.

Value

An object of class gazepoint_fold_diagnostics_validation.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
```

```
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
```

```
  seed = 101L
)
diagnostics <- diagnose_gazepoint_group_folds(folds)
validation <- validate_gazepoint_fold_diagnostics(
  diagnostics
)
validation
```

`validate_gazepoint_group_folds` *Validate group-aware Gazepoint resampling folds*

Description

Validate group-aware Gazepoint resampling folds

Usage

```
validate_gazepoint_group_folds(x)
```

Arguments

x	A `gazepoint_group_folds` object.

Value

An object of class `gazepoint_group_folds_validation`.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
```

```
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
validation <- validate_gazepoint_group_folds(folds)
validation
```

---

validate_gazepoint_handoff

Validate a Gazepoint handoff

Description

Validate a Gazepoint handoff

Usage

```
validate_gazepoint_handoff(x)
```

Arguments

x	A gp3ml_handoff.

Value

A gp3ml_handoff_validation object.

`validate_gazepoint_ml_roles` *Validate outcome, predictor, identifier, and grouping roles*

Description

Validate outcome, predictor, identifier, and grouping roles

Usage

```
validate_gazepoint_ml_roles(data, task, predictors, feature_manifest = NULL)
```

Arguments

data	A data frame containing outcome, predictors, and identifiers.
task	A governed gp3ml_task object.
predictors	Character vector naming intended predictors.
feature_manifest	Optional Gazepoint feature-provenance manifest.

Value

A gp3ml_role_validation object containing the overall status, complete check table, non-passing issues, and optional feature-manifest validation.

Examples

```
example_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  condition = rep(c("A", "B"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
example_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = example_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint all-gaze export"
  ),
  source_table = c("fixations", "all_gaze"),
  transformation = c(
    "Trial-level mean",
    "Baseline-adjusted change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = c("none", "resampling_fold"),
  fold_local_required = c(FALSE, TRUE)
)

validate_gazepoint_ml_roles(
  data = example_data,
  task = task,
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest
```

```
)
```

---

validate_gazepoint_ml_split *Validate a group-aware Gazepoint holdout split*

Description

Validate a group-aware Gazepoint holdout split

Usage

```
validate_gazepoint_ml_split(x)
```

Arguments

x	An object returned by split_gazepoint_ml_data().

Value

An object of class gazepoint_ml_split_validation.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
```

```
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
split <- split_gazepoint_ml_data(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  assessment_prop = 1 / 3,
  seed = 101L
)
validation <- validate_gazepoint_ml_split(split)
validation
```

`validate_gazepoint_model_artifact` *Validate a model artifact*

Description

Validate a model artifact

Usage

```
validate_gazepoint_model_artifact(artifact, verify_hash = TRUE)
```

Arguments

artifact	Artifact to validate.
verify_hash	Whether to recompute the SHA-256 payload hash.

Value

A validation object.

---

validate_gazepoint_model_tuning

Validate governed tuning results

Description

Validate governed tuning results

Usage

```
validate_gazepoint_model_tuning(x)

## S3 method for class 'gp3ml_model_tuning_validation'
print(x, ...)
```

Arguments

x	A gp3ml_model_tuning object.
...	Additional arguments passed to the print method.

Value

A gp3ml_model_tuning_validation.

---

validate_gazepoint_nested_evaluation

Validate a nested evaluation

Description

Validate a nested evaluation

Usage

```
validate_gazepoint_nested_evaluation(x)

## S3 method for class 'gp3ml_nested_evaluation_validation'
print(x, ...)
```

Arguments

x	A gp3ml_nested_evaluation.
...	Additional arguments passed to the print method.

Value

A gp3ml_nested_evaluation_validation.

---

validate_gazepoint_nested_folds

Validate nested grouped folds

Description

Validate nested grouped folds

Usage

```
validate_gazepoint_nested_folds(x)

## S3 method for class 'gp3ml_nested_folds_validation'
print(x, ...)
```

Arguments

x	A gp3ml_nested_folds object.
...	Additional arguments passed to the print method.

Value

A gp3ml_nested_folds_validation object.

---

validate_gazepoint_release_checksums

Validate SHA-256 release checksums

Description

Validate SHA-256 release checksums

Usage

```
validate_gazepoint_release_checksums(manifest, directory = ".")
```

Arguments

manifest	Checksum manifest or path.
directory	Directory containing artifacts.

Value

A validation object.

---

validate_gazepoint_resample_evaluation

Validate a grouped-fold evaluation result

Description

Validate a grouped-fold evaluation result

Usage

```
validate_gazepoint_resample_evaluation(x)

## S3 method for class 'gp3ml_resample_evaluation_validation'
print(x, ...)
```

Arguments

x	A gp3ml_resample_evaluation.
...	Additional arguments passed to the print method.

Value

A gp3ml_resample_evaluation_validation object.

---

validate_gazepoint_research_bundle

Validate a synthetic cross-package research bundle

Description

Validate a synthetic cross-package research bundle

Usage

```
validate_gazepoint_research_bundle(x)
```

Arguments

x	A gp3ml_research_bundle.

Value

A gp3ml_research_bundle_validation.

---

validate_gazepoint_ro_crate

Validate a gp3ml RO-Crate-oriented export

Description

Validate a gp3ml RO-Crate-oriented export

Usage

```
validate_gazepoint_ro_crate(path)
```

Arguments

path	Crate directory or gp3ml_ro_crate.

Value

A validation object.

---

validate_gazepoint_target_uncertainty

Validate target-aligned uncertainty metadata

Description

Validate target-aligned uncertainty metadata

Usage

```
validate_gazepoint_target_uncertainty(x)

## S3 method for class 'gp3ml_uncertainty_validation'
print(x, ...)
```

Arguments

x	A gp3ml_target_uncertainty or gp3ml_resample_uncertainty.
...	Additional arguments passed to the print method.

Value

A gp3ml_uncertainty_validation.

---

validate_gazepoint_transportability

Validate an external transportability report

Description

Validate an external transportability report

Usage

```
validate_gazepoint_transportability(x)

## S3 method for class 'gp3ml_transportability_validation'
print(x, ...)
```

Arguments

x	A gp3ml_transportability_report.
...	Additional arguments passed to the print method.

Value

A gp3ml_transportability_validation.

---

validate_gp3ml_object_contract

Validate an object against the gp3ml public-object contract

Description

Validate an object against the gp3ml public-object contract

Usage

```
validate_gp3ml_object_contract(x, registry = gp3ml_api_contracts())
```

Arguments

x	A gp3ml object.
registry	Contract registry from gp3ml_api_contracts().

Value

A gp3ml_object_contract_validation object.

with_gazepoint_reproducible_output

Evaluate code with deterministic documentation-output settings

Description

Evaluate code with deterministic documentation-output settings

Usage

```
with_gazepoint_reproducible_output(code)
```

Arguments

code	Expression to evaluate.

Value

The value of code.

write_external_validation_report

Write an external-validation report

Description

Write an external-validation report

Usage

```
write_external_validation_report(report, path, overwrite = FALSE)
```

Arguments

report	A gp3ml_external_validation_report object.
path	Destination Markdown file path.
overwrite	Whether an existing file may be replaced.

Value

The destination path, returned invisibly after the Markdown report is written.

Examples

```
training_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
training_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = training_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
model <- train_gazepoint_classifier(
  data = training_data,
  task = task,
  predictors = c("fixation_duration", "pupil_change"),
  engine = "glm",
  seed = 101L
)
external_data <- training_data
external_data$participant_id <- rep(
  sprintf("E%02d", 1:12),
  each = 2
)
external_data$trial_id <- sprintf("ET%02d", 1:24)
external_data$fixation_duration <-
  external_data$fixation_duration + 4
external_data$pupil_change <- cos(seq_len(24) / 4)
validation <- evaluate_external_validation(
  model = model,
  external_data = external_data,
  label = "synthetic_external",
  bootstrap = 10L,
  seed = 101L
)
```

```
report <- create_external_validation_report(validation)
output <- tempfile(fileext = ".md")
write_external_validation_report(report, output)
file.exists(output)
unlink(output)
```

`write_gazepoint_analysis_plan` *Write an analysis plan*

Description

Write an analysis plan

Usage

```
write_gazepoint_analysis_plan(plan, path, format = c("rds", "json", "md"))
```

Arguments

`plan`	Analysis plan.
`path`	Output path.
`format`	`"rds"`, `"json"`, or `"md"`.

Value

Normalized output path, invisibly.

`write_gazepoint_feature_manifest_csv` *Write a Gazepoint feature manifest or validation table to CSV*

Description

Writes a feature manifest or one table from a validated manifest to a UTF-8 CSV file. Existing files are not replaced unless explicitly permitted.

Usage

```
write_gazepoint_feature_manifest_csv(
  x,
  file,
  table = c("manifest", "issues", "checks"),
  overwrite = FALSE,
  na = ""
)
```

Arguments

x	A gazepoint_feature_manifest, compatible data frame, or object returned by validate_gazepoint_feature_manifest().
file	A single output path ending in .csv.
table	Table to export. One of "manifest", "issues", or "checks". Plain manifest inputs support only "manifest".
overwrite	Logical. When FALSE, the default, an existing file causes an error.
na	Character value used for missing values.

Value

The normalized output path, invisibly.

Examples

```
manifest <- create_gazepoint_feature_manifest(
  features = "fixation_duration",
  scientific_source = "Gazepoint fixation export",
  source_table = "fixations",
  transformation = "Trial-level mean",
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)

output <- tempfile(fileext = ".csv")

write_gazepoint_feature_manifest_csv(
  manifest,
  output
)

unlink(output)
```

---

write_gazepoint_fold_diagnostics_csv

Write Gazepoint fold diagnostics to CSV files

Description

Write Gazepoint fold diagnostics to CSV files

Usage

```
write_gazepoint_fold_diagnostics_csv(
  x,
  directory,
  prefix = "gazepoint_fold_diagnostics",
 tables = c("fold_metrics", "repeat_metrics", "outcome_balance", "group_balance",
  "assessment_coverage", "exclusion_summary", "validation_checks", "validation_issues"),
  overwrite = FALSE,
  na = ""
)
```

Arguments

x	A gazepoint_fold_diagnostics object.
directory	Output directory.
prefix	File-name prefix.
tables	Diagnostic tables to export.
overwrite	Whether existing files may be overwritten.
na	String used for missing values.

Value

A named character vector of written file paths, invisibly.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
```

```
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
diagnostics <- diagnose_gazepoint_group_folds(folds)
output_directory <- tempfile()
paths <- write_gazepoint_fold_diagnostics_csv(
  x = diagnostics,
  directory = output_directory,
  tables = c("fold_metrics", "repeat_metrics")
)
basename(unname(paths))
unlink(output_directory, recursive = TRUE)
```

`write_gazepoint_group_folds_csv` *Write group-aware resampling tables to CSV*

Description

Write group-aware resampling tables to CSV

Usage

```
write_gazepoint_group_folds_csv(
  x,
  directory,
  prefix = "gazepoint_group_folds",
  tables = c("assignments", "fold_summary", "group_counts", "group_mapping",
    "validation_checks", "validation_issues", "audit_summary", "audit_checks",
    "audit_issues"),
  include_fold_data = FALSE,
  overwrite = FALSE,
  na = ""
)
```

Arguments

`x`	A `gazepoint_group_folds` object.
`directory`	Output directory.
`prefix`	Non-empty filename prefix.
`tables`	Character vector selecting summary tables.
`include_fold_data`	Logical. Whether every materialized fold partition should also be written.
`overwrite`	Logical. Whether existing files may be replaced.
`na`	Character representation of missing values.

Value

A named character vector of normalized output paths, invisibly.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
```

```
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
folds <- create_gazepoint_group_folds(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  v = 3L,
  repeats = 1L,
  seed = 101L
)
```

```
output_directory <- tempfile()
paths <- write_gazepoint_group_folds_csv(
  x = folds,
  directory = output_directory,
  tables = c("fold_summary", "group_counts")
)
basename(unname(paths))
unlink(output_directory, recursive = TRUE)
```

`write_gazepoint_ml_leakage_audit_csv` *Write a Gazepoint ML leakage-audit table to CSV*

Description

Writes one machine-readable table from a leakage-audit object to a UTF-8 CSV file. Existing files are not replaced unless explicitly permitted.

Usage

```
write_gazepoint_ml_leakage_audit_csv(
  x,
  file,
  table = c("issues", "checks", "partition_summary"),
  overwrite = FALSE,
  na = ""
)
```

Arguments

`x`	An object returned by `audit_gazepoint_ml_leakage()`.
`file`	A single output file path ending in `.csv`.
`table`	The audit table to export. One of `"issues"`, `"checks"`, or `"partition_summary"`.
`overwrite`	Logical. When `FALSE`, the default, an existing output file causes an error.
`na`	Character value used for missing values in the CSV file.

Value

The normalized output path, invisibly.

Examples

```
analysis <- data.frame(
  participant_id = c("P01", "P02"),
  trial_id = c("T01", "T02"),
  outcome = c(0, 1),
  feature = c(1.2, 1.8)
```

```
)

assessment <- data.frame(
  participant_id = c("P03", "P04"),
  trial_id = c("T03", "T04"),
  outcome = c(1, 0),
  feature = c(2.1, 2.4)
)

audit <- audit_gazepoint_ml_leakage(
  analysis = analysis,
  assessment = assessment,
  outcome = "outcome",
  predictors = "feature",
  participant_id = "participant_id",
  trial_id = "trial_id",
  generalization_target = "new_participants"
)

output <- tempfile(fileext = ".csv")

write_gazepoint_ml_leakage_audit_csv(
  audit,
  output,
  table = "checks"
)

unlink(output)
```

`write_gazepoint_ml_split_csv` *Write group-aware split tables to CSV*

Description

Write group-aware split tables to CSV

Usage

```
write_gazepoint_ml_split_csv(
  x,
  directory,
  prefix = "gazepoint_ml_split",
  tables = c("analysis", "assessment", "excluded", "assignment", "summary",
    "group_counts", "checks", "issues"),
  overwrite = FALSE,
  na = ""
)
```

Arguments

x	A gazepoint_ml_split object.
directory	Output directory.
prefix	Filename prefix.
tables	Tables to export.
overwrite	Whether existing files may be replaced.
na	Character representation of missing values.

Value

A named character vector of normalized file paths, invisibly.

Examples

```
example_data <- expand.grid(
  participant_id = sprintf("P%02d", 1:6),
  stimulus_id = sprintf("S%02d", 1:4),
  repetition = 1:2,
  KEEP.OUT.ATTRS = FALSE,
  stringsAsFactors = FALSE
)
example_data$trial_id <- paste0(
  example_data$stimulus_id,
  "_T",
  example_data$repetition
)
participant_number <- as.integer(
  sub("P", "", example_data$participant_id)
)
stimulus_number <- as.integer(
  sub("S", "", example_data$stimulus_id)
)
example_data$outcome <- factor(
  ifelse(
    (participant_number + stimulus_number) %% 2L == 0L,
    "review",
    "pass"
  ),
  levels = c("pass", "review")
)
row_index <- seq_len(nrow(example_data))
example_data$fixation_duration <- 180 + row_index
example_data$pupil_change <- round(
  sin(row_index / 7),
  4
)
example_data$repetition <- NULL
manifest <- create_gazepoint_feature_manifest(
  features = c("fixation_duration", "pupil_change"),
  scientific_source = c(
```

```
    "Gazepoint fixation export",
    "Gazepoint pupil export"
  ),
  source_table = c("fixations", "pupil"),
  transformation = c(
    "Trial-level mean",
    "Trial-level change"
  ),
  availability_stage = "during_exposure",
  prediction_time_available = TRUE,
  preprocessing_scope = "none",
  fold_local_required = FALSE
)
split <- split_gazepoint_ml_data(
  data = example_data,
  outcome = "outcome",
  predictors = c("fixation_duration", "pupil_change"),
  feature_manifest = manifest,
  generalization_target = "new_participants",
  participant_id = "participant_id",
  trial_id = "trial_id",
  stimulus_id = "stimulus_id",
  assessment_prop = 1 / 3,
  seed = 101L
)
output_directory <- tempfile()
paths <- write_gazepoint_ml_split_csv(
  x = split,
  directory = output_directory,
  tables = c("summary", "group_counts")
)
basename(unname(paths))
unlink(output_directory, recursive = TRUE)
```

`write_gazepoint_model_card` *Write a model card*

Description

Write a model card

Usage

```
write_gazepoint_model_card(
  card,
  path,
  format = c("markdown", "json"),
  overwrite = FALSE
)
```

Arguments

card	A gp3ml_model_card object.
path	Destination file path.
format	Output format: Markdown or JSON.
overwrite	Whether an existing file may be replaced.

Value

The destination path, returned invisibly after the model card is written.

Examples

```
training_data <- data.frame(
  participant_id = rep(sprintf("P%02d", 1:12), each = 2),
  trial_id = sprintf("T%02d", 1:24),
  stimulus_id = rep(c("S01", "S02"), 12),
  fixation_duration = 180 + seq_len(24),
  pupil_change = sin(seq_len(24) / 3),
  stringsAsFactors = FALSE
)
training_data$quality_status <- factor(
  c(
    "pass", "review", "pass", "review", "review", "pass",
    "review", "pass", "pass", "review", "review", "pass",
    "review", "pass", "review", "pass", "pass", "review",
    "pass", "review", "review", "pass", "pass", "review"
  ),
  levels = c("pass", "review")
)
task <- declare_gazepoint_task(
  data = training_data,
  outcome = "quality_status",
  purpose = "Predict predefined recording-quality review status",
  task_type = "classification",
  unit_id = "trial_id",
  participant_id = "participant_id",
  stimulus_id = "stimulus_id",
  generalization_target = "new_participants",
  positive = "review"
)
model <- train_gazepoint_classifier(
  data = training_data,
  task = task,
  predictors = c("fixation_duration", "pupil_change"),
  engine = "glm",
  seed = 101L
)
card <- create_gazepoint_model_card(
  model = model,
  intended_use = paste(
    "Support manual review of predefined",
```

```
    "recording-quality status"
  ),
  limitations = "Synthetic example for documentation."
)
output <- tempfile(fileext = ".md")
write_gazepoint_model_card(
  card = card,
  path = output,
  format = "markdown"
)
file.exists(output)
unlink(output)
```

`write_gazepoint_model_tuning` *Write governed tuning and selection tables*

Description

Write governed tuning and selection tables

Usage

```
write_gazepoint_model_tuning(
  x,
  directory,
  prefix = "gazepoint_model_tuning",
  selection = NULL,
  overwrite = FALSE
)
```

Arguments

`x`	A `gp3ml_model_tuning` object.
`directory`	Output directory.
`prefix`	Filename prefix.
`selection`	Optional `gp3ml_model_selection` to record.
`overwrite`	Whether existing files may be replaced.

Value

Named output paths, invisibly.

write_gazepoint_nested_evaluation *Write nested-resampling evaluation tables*

Description

Write nested-resampling evaluation tables

Usage

```
write_gazepoint_nested_evaluation(
  x,
  directory,
  prefix = "gazepoint_nested_evaluation",
  overwrite = FALSE
)
```

Arguments

x	A gp3ml_nested_evaluation.
directory	Output directory.
prefix	Filename prefix.
overwrite	Whether existing files may be replaced.

Value

Named paths, invisibly.

write_gazepoint_release_checksums *Write SHA-256 checksums for release artifacts*

Description

Write SHA-256 checksums for release artifacts

Usage

```
write_gazepoint_release_checksums(files, path = "SHA256SUMS.csv")
```

Arguments

files	Release artifact files.
path	Output checksum manifest.

Value

A gp3ml_release_checksum_manifest.

---

write_gazepoint_release_model_card

Write a release-ready governed model card

Description

Write a release-ready governed model card

Usage

```
write_gazepoint_release_model_card(
  card,
  path,
  format = c("markdown", "json"),
  overwrite = FALSE
)
```

Arguments

card	A gp3ml_release_model_card.
path	Destination path.
format	Markdown or JSON.
overwrite	Whether an existing file may be replaced.

Value

The destination path, invisibly.

---

write_gazepoint_reproducibility_audit

Write a reproducibility-hardening audit

Description

Write a reproducibility-hardening audit

Usage

```
write_gazepoint_reproducibility_audit(
  audit,
  directory = ".",
  prefix = "gp3ml_reproducibility_audit",
  overwrite = FALSE
)
```

Arguments

audit	A gp3ml_reproducibility_audit.
directory	Destination directory.
prefix	File prefix.
overwrite	Whether existing files may be replaced.

Value

Named paths.

---

write_gazepoint_reproducibility_report *Write a reproducibility report*

Description

Write a reproducibility report

Usage

```
write_gazepoint_reproducibility_report(report, path, overwrite = FALSE)
```

Arguments

report	A gp3ml_reproducibility_report object.
path	Destination Markdown file path.
overwrite	Whether an existing file may be replaced.

Value

The destination path, returned invisibly after the reproducibility report is written.

Examples

```
example_data <- data.frame(
  trial_id = sprintf("T%02d", 1:6),
  fixation_duration = c(190, 205, 198, 214, 202, 220),
  stringsAsFactors = FALSE
)
report <- create_gazepoint_reproducibility_report(
  objects = list(
    fixation_values = example_data$fixation_duration
  ),
  data = example_data,
  seeds = list(example = 101L),
  notes = "Synthetic documentation example.",
  project_path = tempdir()
```

```
)
output <- tempfile(fileext = ".md")
write_gazepoint_reproducibility_report(report, output)
file.exists(output)
unlink(output)
```

`write_gazepoint_resample_evaluation` *Write grouped-fold evaluation tables*

Description

Write grouped-fold evaluation tables

Usage

```
write_gazepoint_resample_evaluation(
  x,
  directory,
  prefix = "gazepoint_resample_evaluation",
  overwrite = FALSE
)
```

Arguments

`x`	A `gp3ml_resample_evaluation`.
`directory`	Output directory.
`prefix`	Filename prefix.
`overwrite`	Whether existing files may be replaced.

Value

Named output paths, invisibly.

`write_gazepoint_ro_crate` *Write a minimal RO-Crate-oriented research object*

Description

This helper writes a conservative RO-Crate-oriented JSON-LD metadata file and SHA-256 file hashes. It does not claim formal RO-Crate conformance; use an independent validator when formal conformance is required.

Usage

```
write_gazepoint_ro_crate(
  path,
  files,
  name,
  description,
  creator_name,
  creator_orcid = NULL,
  license = "MIT",
  doi = NULL,
  copy_files = TRUE
)
```

Arguments

path	Output directory.
files	Named or unnamed character vector of files to include.
name	Research-object name.
description	Description.
creator_name	Creator name.
creator_orcid	Optional ORCID URI or identifier.
license	License URI or label.
doi	Optional DOI.
copy_files	Whether to copy files into the crate directory.

Value

A gp3ml_ro_crate.

---

write_gazepoint_target_uncertainty

Write target-aligned uncertainty tables

Description

Write target-aligned uncertainty tables

Usage

```
write_gazepoint_target_uncertainty(
  x,
  directory,
  prefix = "gazepoint_target_uncertainty",
  overwrite = FALSE
)
```

Arguments

x	A gp3ml uncertainty object.
directory	Output directory.
prefix	Filename prefix.
overwrite	Whether existing files may be replaced.

Value

Named paths, invisibly.

---

write_gazepoint_transportability_report *Write an expanded transportability report*

Description

Write an expanded transportability report

Usage

```
write_gazepoint_transportability_report(report, path, overwrite = FALSE)
```

Arguments

report	A gp3ml_transportability_report.
path	Destination Markdown path.
overwrite	Whether an existing file may be replaced.

Value

The destination path, invisibly.

write_gp3ml_api_contracts *Write gp3ml API contracts*

Description

Write gp3ml API contracts

Usage

```
write_gp3ml_api_contracts(
  registry = gp3ml_api_contracts(),
  directory = ".",
  prefix = "gp3ml_api_contracts",
  overwrite = FALSE
)
```

Arguments

registry	Contract registry.
directory	Destination directory.
prefix	File prefix.
overwrite	Whether existing files may be replaced.

Value

Named character vector of written paths.

write_gp3ml_governance_profile *Write a governance profile audit*

Description

Write a governance profile audit

Usage

```
write_gp3ml_governance_profile(audit, path)
```

Arguments

audit	Governance profile audit.
path	Markdown output path.

Value

Output path, invisibly.

Index

apply_gazepoint_calibrator, 5
apply_gazepoint_decision_rule, 6
as_gp3ml_data, 10
assert_gp3ml_engine_available, 7
assert_gp3ml_use_case, 7
assess_gazepoint_calibration, 8
assess_gazepoint_conformal_coverage, 9
audit_gazepoint_abstention, 11
audit_gazepoint_dataset_shift, 11
audit_gazepoint_group_folds, 12
audit_gazepoint_missingness_shift, 13
audit_gazepoint_ml_leakage, 14
audit_gazepoint_ml_leakage(), *97*, *137*
audit_gazepoint_model_robustness, 16
audit_gazepoint_nested_resampling, 17
audit_gazepoint_plan_deviations, 17
audit_gazepoint_reproducibility, 18
audit_gp3ml_api_stability, 19
audit_gp3ml_governance_profile, 19

bake_gazepoint_preprocessor, 20
bootstrap_gazepoint_metrics, 21
bootstrap_gazepoint_metrics_by_unit, 22

capture_gazepoint_environment, 24
collect_gazepoint_fold_predictions, 25
combine_gazepoint_handoffs, 25
compare_gazepoint_environments, 26
compare_gazepoint_models, 26
create_external_validation_report, 27
create_gazepoint_decision_rule, 28
create_gazepoint_feature_manifest, 30
create_gazepoint_feature_manifest(), *42*, *115*
create_gazepoint_group_folds, 31
create_gazepoint_handoff, 34
create_gazepoint_model_artifact, 35
create_gazepoint_model_card, 36
create_gazepoint_nested_folds, 37
create_gazepoint_release_evidence, 39
create_gazepoint_release_model_card, 40
create_gazepoint_reproducibility_report, 41
create_gazepoint_synthetic_manifest, 42
create_gazepoint_synthetic_task, 43
create_gazepoint_tuning_grid, 44
create_gp3ml_governance_profile, 45

declare_gazepoint_analysis_plan, 45
declare_gazepoint_external_dataset, 47
declare_gazepoint_task, 48
diagnose_gazepoint_group_folds, 50

evaluate_external_validation, 52
evaluate_gazepoint_external_transportability, 54
evaluate_gazepoint_feature_stability, 55
evaluate_gazepoint_group_folds, 55
evaluate_gazepoint_missingness_sensitivity, 57
evaluate_gazepoint_nested_resampling, 58
evaluate_gazepoint_seed_stability, 59
evaluate_gazepoint_threshold_stability, 60
evaluate_gazepoint_thresholds, 59

fit_gazepoint_calibrator, 61
fit_gazepoint_conformal, 62
fit_gazepoint_deep_model, 63
fit_gazepoint_model, 65
fit_gazepoint_model(), *56*
fit_gazepoint_preprocessor, 66
fit_gazepoint_preprocessor(), *56*

gazepoint_classification_metrics, 68

gazepoint_performance_metrics, 69
gazepoint_regression_metrics, 71
gp3ml_api_contracts, 71
gp3ml_available_engines, 72
gp3ml_engine_capabilities, 72
gp3ml_interop_contracts, 73
gp3ml_object_schema, 73
gp3ml_prohibited_uses, 74

integrate_black_box_model, 74

lock_gazepoint_analysis_plan, 76

normalize_gazepoint_artifact_text, 76

plot.gp3ml_abstention_audit, 77
plot.gp3ml_api_stability_audit, 77
plot.gp3ml_conformal_coverage, 78
plot.gp3ml_dataset_shift_audit, 78
plot.gp3ml_engine_capabilities, 79
plot.gp3ml_environment_comparison, 79
plot.gp3ml_governance_profile_audit, 80
plot.gp3ml_handoff_validation, 80
plot.gp3ml_model_artifact_validation, 81
plot.gp3ml_model_robustness_audit, 81
plot.gp3ml_plan_deviation_audit, 82
plot.gp3ml_release_checksum_validation, 82
plot.gp3ml_reproducibility_audit, 83
plot.gp3ml_research_bundle_validation, 83
plot.gp3ml_ro_crate_validation, 84
plot.gp3ml_threshold_evaluation, 84
predict.gp3ml_model, 85
predict_gazepoint_interval, 86
predict_gazepoint_set, 87
print.gazepoint_feature_manifest_validation, 87
print.gazepoint_fold_diagnostics, 88
print.gazepoint_fold_diagnostics_validation, 90
print.gazepoint_group_folds, 91
print.gazepoint_group_folds_audit, 93
print.gazepoint_group_folds_validation, 95
print.gazepoint_ml_leakage_audit, 97
print.gazepoint_ml_split, 98
print.gazepoint_ml_split_validation, 99
print.gp3ml_external_dataset_declaration *(*declare_gazepoint_external_dataset*)*, 47
print.gp3ml_model_selection *(*select_gazepoint_model*)*, 102
print.gp3ml_model_tuning *(*tune_gazepoint_model*)*, 112
print.gp3ml_model_tuning_validation *(*validate_gazepoint_model_tuning*)*, 124
print.gp3ml_nested_evaluation *(*evaluate_gazepoint_nested_resampling*)*, 58
print.gp3ml_nested_evaluation_validation *(*validate_gazepoint_nested_evaluation*)*, 124
print.gp3ml_nested_folds *(*create_gazepoint_nested_folds*)*, 37
print.gp3ml_nested_folds_validation *(*validate_gazepoint_nested_folds*)*, 125
print.gp3ml_nested_resampling_audit *(*audit_gazepoint_nested_resampling*)*, 17
print.gp3ml_release_evidence *(*create_gazepoint_release_evidence*)*, 39
print.gp3ml_release_model_card *(*create_gazepoint_release_model_card*)*, 40
print.gp3ml_resample_evaluation *(*evaluate_gazepoint_group_folds*)*, 55
print.gp3ml_resample_evaluation_validation *(*validate_gazepoint_resample_evaluation*)*, 126
print.gp3ml_resample_performance_summary *(*summarize_gazepoint_resample_performance*)*, 108
print.gp3ml_resample_uncertainty *(*summarize_gazepoint_resample_uncertainty*)*, 109
print.gp3ml_target_uncertainty *(*bootstrap_gazepoint_metrics_by_unit*)*, 23

print.gp3ml_transportability_report (evaluate_gazepoint_external_transportability), 54
print.gp3ml_transportability_validation (validate_gazepoint_transportability), 128
print.gp3ml_tuning_grid (create_gazepoint_tuning_grid), 44
print.gp3ml_uncertainty_validation (validate_gazepoint_target_uncertainty), 127

restore_gazepoint_model_artifact, 101

select_gazepoint_model, 102
select_gazepoint_threshold, 103
simulate_gazepoint_governed_data, 104
simulate_gazepoint_governed_data(), *43*
simulate_gazepoint_research_handoffs, 105
split_gazepoint_ml_data, 105
split_gazepoint_ml_data(), *122*
summarize_gazepoint_resample_performance, 108
summarize_gazepoint_resample_uncertainty, 109
summarize_gazepoint_shift, 109

test_gazepoint_model_portability, 110
train_gazepoint_classifier, 111
tune_gazepoint_model, 112

validate_gazepoint_analysis_plan, 113
validate_gazepoint_conformal, 114
validate_gazepoint_decision_rule, 114
validate_gazepoint_environment, 115
validate_gazepoint_feature_manifest, 115
validate_gazepoint_feature_manifest(), *31*, *87*, *132*
validate_gazepoint_fold_diagnostics, 116
validate_gazepoint_group_folds, 118
validate_gazepoint_handoff, 119
validate_gazepoint_ml_roles, 120
validate_gazepoint_ml_split, 122
validate_gazepoint_ml_split(), *100*
validate_gazepoint_model_artifact, 123
validate_gazepoint_model_tuning, 124
validate_gazepoint_nested_evaluation, 124
validate_gazepoint_nested_folds, 125
validate_gazepoint_release_checksums, 125
validate_gazepoint_resample_evaluation, 126
validate_gazepoint_research_bundle, 126
validate_gazepoint_ro_crate, 127
validate_gazepoint_target_uncertainty, 127
validate_gazepoint_transportability, 128
validate_gp3ml_object_contract, 128

with_gazepoint_reproducible_output, 129
write_external_validation_report, 129
write_gazepoint_analysis_plan, 131
write_gazepoint_feature_manifest_csv, 131
write_gazepoint_fold_diagnostics_csv, 132
write_gazepoint_group_folds_csv, 134
write_gazepoint_ml_leakage_audit_csv, 137
write_gazepoint_ml_split_csv, 138
write_gazepoint_model_card, 140
write_gazepoint_model_tuning, 142
write_gazepoint_nested_evaluation, 143
write_gazepoint_release_checksums, 143
write_gazepoint_release_model_card, 144
write_gazepoint_reproducibility_audit, 144
write_gazepoint_reproducibility_report, 145
write_gazepoint_resample_evaluation, 146
write_gazepoint_ro_crate, 146
write_gazepoint_target_uncertainty, 147
write_gazepoint_transportability_report, 148
write_gp3ml_api_contracts, 149
write_gp3ml_governance_profile, 149