

# Package ‘mitools’

October 13, 2022

**Title** Tools for Multiple Imputation of Missing Data

**Version** 2.4

**Author** Thomas Lumley

**Description** Tools to perform analyses and combine results from multiple-imputation datasets.

**Maintainer** Thomas Lumley <t.lumley@auckland.ac.nz>

**Suggests** RODBC, foreign

**Imports** DBI, methods, stats

**License** GPL-2

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2019-04-26 05:00:03 UTC

## R topics documented:

imputationList . . . . .	2
MIcombine . . . . .	3
MIextract . . . . .	4
pisamaths . . . . .	5
smi . . . . .	7
with.imputationList . . . . .	8
withPV . . . . .	9

<b>Index</b>	<b>11</b>
--------------	-----------

---

imputationList                      *Constructor for imputationList objects*

---

### Description

Create and update imputationList objects to be used as input to other MI routines.

### Usage

```
imputationList(datasets,...)
## Default S3 method:
imputationList(datasets,...)
## S3 method for class 'character'
imputationList(datasets,dbtype,dbname,...)
## S3 method for class 'imputationList'
update(object,...)
## S3 method for class 'imputationList'
rbind(...)
## S3 method for class 'imputationList'
cbind(...)
```

### Arguments

datasets	a list of data frames corresponding to the multiple imputations, or a list of names of database tables or views
dbtype	"ODBC" or a database driver name for DBI::dbDriver()
dbname	Name of the database
object	An object of class imputationList
...	Arguments tag=expr to update will create new variables tag by evaluating expr in each imputed dataset. Arguments to imputationList() are passed to the database driver

### Details

When the arguments to imputationList() are character strings a database-based imputation list is created. This can be a database accessed through ODBC with the RODBC package or a database with a DBI-compatible driver. The dbname and ... arguments are passed to dbConnect() or odbcConnect() to create a database connection. Data are read from the database as needed.

For a database-backed object the update() method creates variable definitions that are evaluated as the data are read, so that read-only access to the database is sufficient.

### Value

An object of class imputationList or DBimputationList

**Examples**

```
## Not run:
## CRAN doesn't like this example
data.dir <- system.file("dta",package="mitools")
files.men <- list.files(data.dir,pattern="m\\.\\dta$",full=TRUE)
men <- imputationList(lapply(files.men, foreign::read.dta))
files.women <- list.files(data.dir,pattern="f\\.\\dta$",full=TRUE)
women <- imputationList(lapply(files.women, foreign::read.dta))
men <- update(men, sex=1)
women <- update(women,sex=0)
all <- rbind(men,women)
all <- update(all, drinkreg=as.numeric(drkfre)>2)
all

## End(Not run)
```

MIcombine

*Multiple imputation inference***Description**

Combines results of analyses on multiply imputed data sets. A generic function with methods for `imputationResultList` objects and a default method. In addition to point estimates and variances, MIcombine computes Rubin's degrees-of-freedom estimate and rate of missing information.

**Usage**

```
MIcombine(results, ...)
## Default S3 method:
MIcombine(results,variances,call=sys.call(),df.complete=Inf,...)
## S3 method for class 'imputationResultList'
MIcombine(results,call=NULL,df.complete=Inf,...)
```

**Arguments**

<code>results</code>	A list of results from inference on separate imputed datasets
<code>variances</code>	If <code>results</code> is a list of parameter vectors, <code>variances</code> should be the corresponding variance-covariance matrices
<code>call</code>	A function call for labelling the results
<code>df.complete</code>	Complete-data degrees of freedom
<code>...</code>	Other arguments, not used

**Details**

The results argument in the default method may be either a list of parameter vectors or a list of objects that have coef and vcov methods. In the former case a list of variance-covariance matrices must be supplied as the second argument.

The complete-data degrees of freedom are used when a complete-data analysis would use a t-distribution rather than a Normal distribution for confidence intervals, such as some survey applications.

**Value**

An object of class MIresult with summary and print methods

**References**

~put references to the literature/web site here ~

**See Also**

[MIextract, with.imputationList](#)

**Examples**

```
data(smi)
models<-with(smi, glm(drinkreg~wave*sex,family=binomial()))
summary(MIcombine(models))

betas<-MIextract(models,fun=coef)
vars<-MIextract(models, fun=vcov)
summary(MIcombine(betas,vars))
```

---

MIextract

*Extract a parameter from a list of results*


---

**Description**

Used to extract parameter estimates and standard errors from lists produced by [with.imputationList](#).

**Usage**

```
MIextract(results, expr, fun)
```

**Arguments**

results	A list of objects
expr	an expression
fun	a function of one argument

**Details**

If `expr` is supplied, it is evaluated in each element of `results`. Otherwise each element of `results` is passed as an argument to `fun`.

**Value**

A list

**See Also**

[with.imputationList](#), [MIcombine](#)

**Examples**

```
data(smi)
models<-with(smi, glm(drinkreg~wave*sex,family=binomial()))

betas<-MIextract(models,fun=coef)
vars<-MIextract(models, fun=vcov)
summary(MIcombine(betas,vars))
```

---

`pisamaths`

*Maths Performance Data from the PISA 2012 survey in New Zealand*

---

**Description**

Data on maths performance, gender, some problem-solving variables and some school resource variables. This is actually a weighted survey: see `withPV.survey.design` in the `survey` package for a better analysis.

**Usage**

```
data("pisamaths")
```

**Format**

A data frame with 4291 observations on the following 26 variables.

SCHOOLID School ID

CNT Country id: a factor with levels New Zealand

STRATUM a factor with levels NZL0101 NZL0102 NZL0202 NZL0203

OECD Is the country in the OECD?

STIDSTD Student ID

ST04Q01 Gender: a factor with levels Female Male

ST14Q02 Mother has university qualifications No Yes

ST18Q02 Father has university qualifications No Yes

MATHEFF Mathematics Self-Efficacy: numeric vector

OPENPS Mathematics Self-Efficacy: numeric vector

PV1MATH,PV2MATH,PV3MATH,PV4MATH,PV5MATH 'Plausible values' (multiple imputations) for maths performance

W\_FSTUWT Design weight for student

SC35Q02 Proportion of maths teachers with professional development in maths in past year

PCGIRLS Proportion of girls at the school

PROPMA5A Proportion of maths teachers with ISCED 5A (math major)

ABGMATH Does the school group maths students: a factor with levels No ability grouping between any classes One of these forms of ability grouping between classes for s One of these forms of ability grouping for all classes

SMRATIO Number of students per maths teacher

W\_FSCHWT Design weight for school

condwt Design weight for student given school

### Source

A subset extracted from the PISA2012lite R package, <https://github.com/pbiecek/PISA2012lite>

### References

OECD (2013) PISA 2012 Assessment and Analytical Framework: Mathematics, Reading, Science, Problem Solving and Financial Literacy. OECD Publishing.

### Examples

```
data(pisamaths)

means<-withPV(list(maths~PV1MATH+PV2MATH+PV3MATH+PV4MATH+PV5MATH), data=pisamaths,
  action= quote(by(maths, ST04Q01, mean)), rewrite=TRUE)
means

models<-withPV(list(maths~PV1MATH+PV2MATH+PV3MATH+PV4MATH+PV5MATH), data=pisamaths,
  action= quote(lm(maths~ST04Q01*PCGIRLS)), rewrite=TRUE)
summary(MIcombine(models))
```

---

**smi***Multiple imputations*

---

**Description**

An `imputationList` object containing five imputations of data from the Victorian Adolescent Health Cohort Study.

**Usage**

```
data(smi)
```

**Format**

The underlying data are in a data frame with 1170 observations on the following 12 variables.

**id** a numeric vector

**wave** a numeric vector

**mmetro** a numeric vector

**parsmk** a numeric vector

**drkfre** a factor with levels Non drinker not in last wk <3 days last wk >=3 days last wk

**alcdos** a factor with levels Non drinker not in last wk av <5units/drink\_day av =>5units/drink\_day

**alcdhi** a numeric vector

**smk** a factor with levels non/ex-smoker <6 days 6/7 days

**cistot** a numeric vector

**mdrkfre** a numeric vector

**sex** a numeric vector

**drinkreg** a logical vector

**Source**

Carlin, JB, Li, N, Greenwood, P, Coffey, C. (2003) "Tools for analysing multiple imputed datasets" *The Stata Journal* 3; 3: 1-20.

**Examples**

```
data(smi)
with(smi, table(sex, drkfre))
model1<-with(smi, glm(drinkreg~wave*sex, family=binomial()))
MIcombine(model1)
summary(MIcombine(model1))
```

---

with.imputationList    *Evaluate an expression in multiple imputed datasets*

---

## Description

Performs a computation of each of imputed datasets in data

## Usage

```
## S3 method for class 'imputationList'  
with(data, expr, fun, ...)
```

## Arguments

data	An imputationList object
expr	An expression
fun	A function taking a data frame argument
...	Other arguments, passed to fun

## Details

If expr is supplied, evaluate it in each dataset in data; if fun is supplied, it is evaluated on each dataset. If all the results inherit from "imputationResult" the return value is an imputationResultList object, otherwise it is an ordinary list.

## Value

Either a list or an imputationResultList object

## See Also

[imputationList](#)

## Examples

```
data(smi)  
models<-with(smi, glm(drinkreg~wave*sex,family=binomial()))  
tables<-with(smi, table(drkfre,sex))  
with(smi, fun=summary)
```



---

withPV                      *Analyse plausible values in surveys*

---

### Description

Repeats an analysis for each of a set of 'plausible values' in a data set, returning a list suitable for MIcombine. That is, the data set contains some sets of columns where each set are multiple imputations of the same variable. With `rewrite=TRUE`, the action is rewritten to reference each plausible value in turn; with `coderewrite=FALSE` a new data set is constructed for each plausible value, which is slower but more general.

### Usage

```
withPV(mapping, data, action, rewrite=TRUE, ...)
## Default S3 method:
withPV(mapping, data, action, rewrite=TRUE,...)
```

### Arguments

mapping	A formula or list of formulas describing each variable in the analysis that has plausible values. The left-hand side of the formula is the name to use in the analysis; the right-hand side gives the names in the dataset.
data	A data frame. Methods for <code>withPV</code> dispatch on this argument, so can be written for, eg, survey designs or out-of-memory datasets.
action	With <code>rewrite=TRUE</code> , a quoted expression specifying the analysis, or a function taking a data frame as its only argument. With <code>rewrite=FALSE</code> , A function taking a data frame as its only argument, or a quoted expression with <code>.DATA</code> referring to the newly-created data frame to be used.
rewrite	Rewrite action before evaluating it (versus constructing new data sets)
...	For methods

### Value

A list of the results returned by each evaluation of `action`, with the call as an attribute.

### Note

I would be interested in seeing naturally-occurring examples where `rewrite=TRUE` does not work

### See Also

[pisamaths](#)  
[with.imputationList](#)

**Examples**

```
data(pisamaths)

models<-withPV(list(maths~PV1MATH+PV2MATH+PV3MATH+PV4MATH+PV5MATH), data=pisamaths,
  action= quote(lm(maths~ ST04Q01*(PCGIRLS+SMRATIO)+MATHEFF+OPENPS,
    data=.DATA)),
  rewrite=FALSE
)

summary(MIcombine(models))

## equivalently
models2<-withPV(list(maths~PV1MATH+PV2MATH+PV3MATH+PV4MATH+PV5MATH), data=pisamaths,
  action=quote( lm(maths~ST04Q01*(PCGIRLS+SMRATIO)+MATHEFF+OPENPS)), rewrite=TRUE)

summary(MIcombine(models2))
```

# Index

- \* **datasets**
  - pisamaths, 5
  - smi, 7
- \* **htest**
  - MIcombine, 3
- \* **manip**
  - imputationList, 2
  - MIcombine, 3
  - MIextract, 4
  - with.imputationList, 8

cbind.imputationList (imputationList), 2

dim.imputationList (imputationList), 2

dimnames.imputationList  
(imputationList), 2

imputationList, 2, 8

MIcombine, 3, 5

MIextract, 4, 4

pisamaths, 5, 9

print.imputationList (imputationList), 2

print.MIresult (MIcombine), 3

rbind.imputationList (imputationList), 2

smi, 7

summary.MIresult (MIcombine), 3

update.imputationList (imputationList),  
2

vcov.MIresult (MIcombine), 3

with.imputationList, 4, 5, 8, 9

withPV, 9