Package 'pro'

May 9, 2026

Type Package

Title Point-Process Response Model for Optogenetics

Version 0.1.1

Date 2015-09-17

Author Xi (Rossi) LUO with contributions from Dylan Small and Vikaas Sohal

Maintainer Xi (Rossi) LUO <xi.rossi.luo@gmail.com>

Suggests cin

Description Optogenetics is a new tool to study neuronal circuits that have been genetically modified to allow stimulation by flashes of light. This package implements the methodological framework, Point-process Response model for Optogenetics (PRO), for analyzing data from these experiments. This method provides explicit nonlinear transformations to link the flash point-process with the spiking point-process. Such response functions can be used to provide important and interpretable scientific insights into the properties of the biophysical process that governs neural spiking in response to optogenetic stimulation.

License GPL-2

NeedsCompilation no

Repository CRAN

Date/Publication 2015-09-17 22:50:12

Contents

model.pro 2
pro 3
sim.lif 3

Index **5**

model.pro *Model matrix for point-process responses*

Description

Constructs a data.frame to be fitted using pro. Reference: X Luo, S Gee, V Sohal, D Small (In Press). A Point-process Response Model for Optogenetics Experiments on Neural Circuits. _Statistics in Medicine_.

Usage

```
model.pro(spike, flash, fixed = NULL, kv = F)
```

Arguments

spike	A binary vector represents spiking (1) or no spiking (0).
flash	A binary vector of the same length of spike, 1 for flashing and 0 for non-flashing.
fixed	Whether a fixed time window of spike/flash history should be used. If it is NULL, a varying time window of history will be used as described in the reference. If it is a integer j, a fixed window from index t-j to t will be used.
kv	Whether the history dependence model in Kass and Ventura (2001) (A Spike-Train Probability Model, Neural Computation 13, 1713-1720) should be employed. This differs from the history dependence model in the reference.

Value

a data.frame of the three response functions (PF, CF, SF) and other intermediate functions (for future modeling use).

Examples

```
n <- 500
set.seed(100)
re <- sim.lif(n, rbinom(n, 1, 0.14), 7, 3)
d <- model.pro(re$sbin, re$I)
d[1:10, ]
```

pro *Fit the PRO model*

Description

Fit the PRO model to data. Reference: X Luo, S Gee, V Sohal, D Small (In Press). A Point-process Response Model for Optogenetics Experiments on Neural Circuits. _Statistics in Medicine_.

Usage

```
pro(spike, flash, ...)
```

Arguments

spike	A binary vector represents spiking (1) or no spiking (0).
flash	A binary vector of the same length of spike, 1 for flashing and 0 for non-flashing.
...	Additional parameters, see model.pro.

Value

a glm object of the fitted PRO coefficients.

Examples

```
n <- 500
set.seed(100)
re <- sim.lif(n, rbinom(n, 1, 0.14), 7, 3)
fit.pro <- pro(re$sbin, re$I)
summary(fit.pro)
```

sim.lif *Simulate optogenetic stimulation on a leaky-integrate-fire neuron*

Description

Simulate various kinds of neural measures (e.g. membrane potentials and spikes) from a LIF neuron.

Usage

```
sim.lif(n, I, C, R, Vth = 1, V0 = 0, bin = 5, dt = 0.05)
```

Arguments

n	Number of time bins. The total time is n times bin.
I	Input stimulus vector of length n.
C	Membrane capacitance of the simulated neuron.
R	Membrane resistance of the simulated neuron.
Vth	Membrane potential threshold for spiking.
V0	Membrane potential reset value after spiking.
bin	Time length for each time bin. Default 5 millisecond.
dt	Time length for each simulation step. Default 0.05 millisecond.

Value

a list of simulated neural spikes, optogenetic light flashes, and simulation parameters.

Examples

```
n<- 500
set.seed(100)
re <- sim.lif(n, rbinom(n, 1, 0.14), 7, 3)
```

Index

glm, *3*

model.pro, 2, *3*

pro, *2*, 3

sim.lif, 3